

WATERPROOF pH-METER CP-401

- Used for accurate pH, temperature and redox potential measurements.
- Useful for measurements in the field and laboratory.
- Waterproof housing (IP-66) facilitates working in difficult conditions.
- Low weight and small size make working in the field easier.
- Meter is equipped with an large, easy to read backlight LCD display with brightness control.
- Possibility of making measurements in clean water, sewage soil, etc., depending on the kind of applied pH electrode.
- Calibration of the pH electrode : 1 ÷ 5 points.
- Automatic detection of buffer solutions, their values may be changed by the user in the given range.
- Automatic correction of the pH sample solution value changes, along with the temperature changes for NIST standards.
- Automatic or manual temperature compensation.
- Storage of 3 electrodes characteristics enables to replace them quickly – feature very useful during field work.
- The date of calibration of each pH electrode stored by the meter, with possibility of signalling moment when next calibration should be done.
- Automatic evaluation of the of electrode's condition.
- Precise Redox potential measurement (accuracy 0.1 mV).
- Clock with date.
- Auto switch off function, with time set by user, to protect the battery against discharging.
- Internal datalogger for up to 4000 sets of results collected in series or singly with temperature time and date.
- The results and calibration data are stored in non-volatile memory.
- Possibility of connecting with a PC using RS-232 output or by USB using optional adapter.
- The meter meets the GLP requirements
- 24 months of warranty for the meter.
- **CP-401** pH-meter received a Golden Medal on international fair EUROLAB.



Function	pH	mV	°C
Range	-2.000 ÷ 16.000 pH	±1999.9 mV	-50.0 ÷ 199.9 °C
Resolution	0.001 pH or 0.01 pH	0.1mV	0.1 °C
Accuracy* (± 1 digit)	±0.002 pH*	±0.1 mV	±0.1 °C*
Input impedance	10 ¹² Ω		
Temp. compensation range	-5 ÷ 110.0 °C		
Power	rechargeable battery 2 x AA 1.5V, 6V power adapter		
Dimens. (mm) / Weight	L=149, W=82, H=22 / 220 g		

* Accuracy of the meter. The total error is dependent on the sum of probe's and meter's errors.

ELMETRON[®] Sp. j.
 41-814 Zabrze ul. Witosa 10 POLAND
 tel. +48 32 2738106 fax +48 32 2738114
www.elmetron.pl e-mail: info@elmetron.com.pl