

Water-Proof Multifunction Meter

CPC-401



SECHANG INSTRUMENTS

1.

가

(CPC-401)

(9V x 1)

(,)

pH

Calibration Solution pH 4.00 500mL

Calibration Solution pH 7.00 500mL

Calibration Solution Conductivity 1.413mS/cm 480mL

ORP

Optional

Stabile Voltage 12V AC Adaptor

Calibration Solution pH 10.00

Calibration Solution ORP 86 mV()

Calibration Solution ORP 255 mV()

Calibration Solution ORP 455 mV()

Calibration Solution TDS 1382 ppm

Calibration Solution NaCl 3g/L

Calibration Solution NaCl 30g/L

:

:



2.

CPC-401 가 가 가

shut-off, 가 "LOBAT", 가

3.

- F* BNC pH, ORP,
- t*
- F1*
- RS* RS-232C
- P* 12V AC Adaptor



가 20 가
CPC-401 Function Function 가

CPC-401 가

4.

- Mode , 가 가 .
- 1. Mode (Lo) (Hi) , rES .
- 2. Mode (E2,E3) , (E1, CPC-401
- 3 .
- 4. , .
- 4. , .
- : , 가
- : 가 1 .
- , 10 .



5.

CPC-401

5.1 pH

Mode (Ust,
Aut) (pH
2.00, pH 4.00, pH 7.00, pH 10.00, pH 12.00)

3 pH7.00, pH4.01,
(2)

pH ERH111

(pH 7.00)

CAL
'CAL' 가

Errrk 가

(pH 4.01) ~

3 (pH 10.00) ~

Function

(ORP; mV)



5.2 (COND)

Mode , 가

Mode ,

.) (*Cond*

Mode (Unit)
(*Cond*), NaCl
(*NaCl*), KCl (*KCl*), (tdS) 4가
가

:

Mode , TDS TDS

Mode ,
가
1413uS/cm

(1413uS/cm)

CAL
'CAL' 가

Errrk 가

Function



