

## LABORATORY pH / ION METER CPI-505

- Measures accurately: pH, redox potential, ion concentration in pX, g/l, M/l, or ppm and temperature (°C).
- The meter is equipped with large, easy-to-read backlit LCD display with brightness control.
- Enables ion concentration measurements of monovalent, bivalent, negative and positive ions.
- The range of the meter enables work with all available ion selective electrodes (ISE), chosen adequately to the kind of measured ion, equipped with BNC 50 connector.
- Entering automatically the molar weight of a particular ion.
- Automatic unit conversion (e.g. mol/l to mg/l).
- Possibility of entering freely chosen values of ion standard solutions.
- Automatic and manual temperature compensation.
- The meter stores 3 characteristics of pH electrodes and ion selective electrodes independently.

### pH measurement:

- Calibration of the pH electrode: 1 ÷ 5 points.
- Automatic pH buffer detection, their value may be set by the user.
- Automatic correction of the stored pH standard value influenced by the temperature change (compliant with NIST).
- Information about the pH electrode's condition.
- Depending on type of the chosen electrode making measurement in pure water, sewage, pastes, etc.
- Internal datalogger for up to 4000 sets of results with temperature, time and date.
- Collecting series of readouts with intervals set by the user.
- Possibility to enter the next calibration date into memory.
- USB output.
- The meter meets the GLP requirements.
- Internal clock with date.
- 24 months of warranty.



Function	pH	mV	Ion ( M/l)	Ion (g/l)	Ion (ppm)	Ion (pX)	°C
<b>Range</b>	-2.000 ÷ 16.000	±1999.9 mV	0 ÷ 100	0 ÷ 1000	0 ÷ 1000 000	-2.00 ÷ 16.00	-50.0 ÷ 199.9
<b>Resolution</b>	0.001 or 0.01	0.1 mV	0.01 / 0.1%	0.01 / 0.1%	0.01 / 0.1%	0.001 / 0.01	0.1 °C*
<b>Accuracy (± 1 digit)</b>	±0.002 pH	±0.1 mV	± 0.25%	± 0.25%	± 0.25%	± 0.002 pX	±0.1°C
<b>Input impedance</b>	10 <sup>12</sup> Ω						
<b>Temp. compens. range</b>	-5 ÷ 110.0 °C						
<b>Dimensions (mm)</b>	L=200, W=180, H=50						
<b>Weight</b>	650 g						

\* The final accuracy depends on the accuracy of the chosen probe.

**ELMETRON®** Sp. j.

41-814 Zabrze ul. Witosa 10 POLAND  
 tel. +48 32 / 2738106 fax +48 32 / 2738114  
[www.elmetron.pl](http://www.elmetron.pl) e-mail: info@elmetron.com.pl