

Thermo Scientific Orion Star A325 pH/ Conductivity Portable Meter

The Thermo Scientific Orion Star A325 pH/Conductivity Portable Meter is the top choice for testing samples anywhere. It is rugged and dependable, making it ideal for every sample, every day, everywhere.



The Thermo Scientific Orion Star A325 pH/Conductivity Portable Meter is the top choice for advanced measurements on location. Get the information you need quickly and easily from the large, backlit graphic LCD display. Informative display shows individual pH/mV/RmV or conductivity/TDS/salinity/resistivity results with temperature, or all results at once. Additional helpful information include electrode status, time, date, sample ID, user ID and calibration points. Advanced features such as stability and averaging options provide additional options allowing for laboratory accuracy everywhere you need it.

Features and Benefits

- Anyone can use this meter with its plain language screen prompts, soft keys that update for easy selection and a multilanguage interface that supports English, Spanish, French, Italian, German and Chinese
- Don't miss a reading – AUTO-READ™ locks in the stable reading on your screen, ready indicator alerts when readings are stable and timed reading gathers data in specific time intervals
- Up to 5 point pH calibration with automatic recognition for USA/NIST and DIN buffers
- Fix pH calibration errors without a complete recalibration with calibration editing
- Selectable cell constant allows for use with 2- or 4-cell conductivity cells
- For advanced accuracy in conductivity readings, selectable reading reference temperatures of 5, 10, 15, 20 or 25 °C with linear, non-linear, nLFu or EP curve options
- Choice of practical salinity or natural sea water curves for salinity readings
- Linear or ISO/EN 27888 curves for TDS
- Non-volatile memory holds up to 5000 data points with time and date stamp
- Easily transfer data and keep meter software up-to-date with the USB and RS232 ports and complimentary data analysis software
- Four AA batteries (included) provide over 800 hours of operation or purchase the universal power adapter (sold separately) to use AC power
- Perfectly portable, waterproof and protected to take anywhere with a IP67-rated housing
- 3 year meter replacement warranty

Thermo Scientific Orion Star A325 pH/Conductivity Portable Meter

Specifications



pH	Range	-2.000 to 20.000	
	Resolution	0.1, 0.01, 0.001	
	Relative Accuracy	±0.002	
	Calibration Points	Up to 5	
	Calibration Editing	Yes	
mV/RmV	Range	±2000.0 mV	
	Resolution	0.1	
	Relative Accuracy	±0.2 mV or ±0.05 % of reading whichever is greater	
	E_H ORP Mode	Yes	
Conductivity	Range	0.001 µS to 3000 mS	
	Resolution	0.001 µS minimum; 4 significant figures minimum	
	Relative Accuracy	0.5 % reading ±1 digit	
	Reference Temperature	5, 10, 15, 20, 25 °C (default)	
	Temperature Compensation	Linear (0 to 10.0 %/°C), nLn, nLFu, EP	
	Compatible Cell Constants	0.001 to 199.9	
	Calibration Points	Up to 5 points	
	Calibration Editing	Yes	
	Resistivity	Range	2 ohm to 100 meg-ohm
		Resolution	2 ohms-cm
Relative Accuracy		0.5 % reading ±1 digit	
Salinity	Type	Practical salinity or natural sea water	
	Range	0.01 to 80.0 ppt NaCl equivalent; 0.01 to 42 ppt practical salinity	
	Resolution	0.01	
	Relative Accuracy	±0.1	
TDS	Range	0 to 200 ppt	
	Resolution	4 significant digits	
	Relative Accuracy	±0.5 % reading ±1 digit	
	TDS Factor Range	Linear 0.01 to 10.00, default 0.49	
Temperature	Range	-5 to 105 °C, 23 to 221 °F	
	Resolution	0.1	
	Relative Accuracy	±0.1	
	Offset Calibration	1 point	
Datalogging	Number of Points	2000 with time and date stamp	
	Log Function	Manual, ready (include AUTO-READ™), timed Delete individual points, group of points or all	
	Log Edit		
Inputs	pH Electrode	BNC, reference pin	
	Conductivity with Temperature Probe or ATC Probe	8-pin mini-DIN	
Output		RS232, USB	
Power	AC Adapter	Optional – universal, 100-240 VAC	
	Battery Power	Included – 4 AAs	
	Battery Life	800 hrs	

Ordering Information

Cat. No.	Description
STARA3250	Orion STAR A325 pH/Conductivity Portable Multiparameter Meter - Four AA batteries (installed)
STARA3255	Orion STAR A325 pH/Conductivity Portable Multiparameter Meter Kit - 8107UWMMD Orion ROSS Triode 3-in-1 pH/ATC probe, 3m cable - 013010MD Orion DuraProbe conductivity cell, 3m cable - 910410 Orion pH 4.01 buffer, 10 pouches - 910710 Orion pH 7.00 buffer, 10 pouches - 911010 Orion pH 10.01 buffer, 10 pouches - 810001 Orion ROSS electrode storage solution, 475 mL - 01100710 Orion 1413 µS conductivity standard, 10 pouches - 911110 rinse solution, 10 pouches - Protective armor with electrode holder - Hard carrying case - Four AA batteries (installed)
Accessories	
STARA-CS	Hard carrying case for Orion Star A-series portable meters
STARA-AR	Armor for Orion Star A-series portable meters, includes electrode holders for pH, conductivity and DO probes
STARA-ESPH	pH electrode holder for Orion Star A-series armor
STARA-ESCD	Conductivity and DO probe holder for Orion Star A-series armor
8107UWMMD	Orion ROSS Triode 3-in-1 pH/ATC probe, gel-filled, 3m cable
013010MD	Orion DuraProbe conductivity cell with 3m cable, 4-cell, K=0.475
1010003	Optional universal power adapter, 100-240 V, 50/60 Hz
910410	Orion pH 4.01 buffer pouches, 10/pk
910710	Orion pH 7.00 buffer pouches, 10/pk
911010	Orion pH 10.01 buffer pouches, 10/pk
911110	Orion pH rinse solution pouches, 10/pk
011008	Orion conductivity standard, 100 µS/cm, 5 x 60 mL bottles
01100710	Orion conductivity standard pouches, 1413 µS/cm, 10/pk
01100610	Orion conductivity standard pouches, 12.9 mS/cm, 10/pk
1010001	Orion conductivity calibration resistor kit

For more information, contact your local Thermo Scientific products dealer or call our customer and technical service experts at 1-800-225-1480 (for the US and Canada) or visit www.thermoscientific.com/water.

©2011 Thermo Fisher Scientific Inc. All rights reserved. All trademarks are the property of Thermo Fisher Scientific Inc. and its subsidiaries. ROSS and the COIL tradenames are trademarks of Thermo Fisher Scientific Inc. US Patent 6,793,787.



S-STARA325-E-0811-RevA

Water Analysis Instruments
www.thermoscientific.com/water

North America
166 Cummings Center
Beverly, MA 01915 USA
Toll Free: 1-800-225-1480
Tel: 1-978-232-6000
info.water@thermo.com

Netherlands
Tel: (31) 033-2463887
info.water.uk@thermo.com

China
Tel: (86) 21-68654588
wai.asia@thermofisher.com

India
Tel: (91) 22-4175-8800
wai.asia@thermofisher.com

Singapore
Tel: (65) 6778-6876
wai.asia@thermofisher.com

Japan
Tel: (81) 045-453-9175
wai.asia@thermofisher.com

Australia
Tel: (613) 9757-4300
infowaterau@thermofisher.com

Thermo
SCIENTIFIC