## Measuring cables

CPK9 special measuring cable

- For sensors with TOP68 plug-in head, for high-temperature and high-pressure applications, IP 68
- Ordering acc. to product structure, see Technical Information (TI118C/07/en)

CPK1 special measuring cable

- For pH/ORP electrodes with GSA plug-in head
- Ordering acc. to product structure, see Technical Information (TI118C/07/en)

CPK12 special measuring cable

- For pH/ORP glass electrodes and ISFET sensors with TOP68 plug-in head
- Ordering acc. to product structure, see Technical Information (TI118C/07/en)

CYK10 Memosens data cable

- For digital sensors with Memosens technology
- Ordering according to product structure, see below

	Certi	ficates			
	A	Standard, non Ex			
	G	ATEX II 1G EEx ia IIC T6/T4			
		Cable length			
		03	Cable 1	length: 3 m (9.8 ft)	
		05	Cable l	length: 5 m (16 ft)	
		10	Cable l	length: 10 m (33 ft)	
		15	Cable l	length: 15 m (49 ft)	
		20	Cable length: 20 m (66 ft)		
		25	Cable length: 25 m (82 ft)		
		88	m length		
		89	ft le	ft length	
			Ready-made		
			1	Wire terminals	
CYK10-				complete order code	



## Note!

Ex versions of CYK10 are indicated by an orange-red coupling end.

## **Instruments International**

n ress auser
Instruments International
ae enstrasse
eina
it erlan
el
a
en ress om

in o ii en ress om



People for Process Automation