

PRODUCT PROFILE



MONITOR™ for RESIDUAL GLUCOSE

Product Code 5188

WHAT does this product do?

Serim® Monitor™ for Residual Glucose detects the presence of glucose (dextrose) in the final discharge water after washing tanker/trailers transporting liquid sweeteners.

WHY should I use this product?

The Serim Monitor for Residual Glucose will help achieve compliance with applicable regulatory standards [e.g., Good Manufacturing Practices (GMP), customer requirements and industry standards].

WHERE do I use this product?

On a predetermined schedule, test the final discharge water draining from the trailer with a glucose test strip. If the test result is positive, review the wash procedures and take the appropriate corrective action.¹

After washing with hot water, hoses and other removable components should be tested for the presence of glucose.

HOW to use this product?

Serim Monitor strips are supplied in ready-to-use form. When placed in contact with the sample according to the directions for use (see below), the indicator pad changes color relative to the presence of residual glucose.

Ordering Information

Serim Monitor for Residual Glucose

- Product Code 5188
1 bottle of 100 strips



Results: Presence of Glucose



Negative

Positive

Positive

Diagrams are for illustration purposes only.
Always use the color blocks on the actual bottle label to interpret results.

Test Method	Immersion
Test Strip Technique	Start timer and immerse indicator pad in the rinse solution. Remove immediately .
Results	Between 30 and 60 seconds after immersion, compare the color of the indicator pad to color chart on the bottle label.

Store bottles of Serim MONITOR Test Strips at temperatures between 15° – 30°C (59° – 86°F).
The lot number and expiration date are printed on the bottom of each bottle.

PRODUCT PROFILE

Related Products

5155 Monitor for Chlorine 0-10 ppm
5148 Monitor for Chlorine 0-300 ppm²
5161 Monitor for Chlorine 100-750 ppm
5162 Monitor for pH 0-14³

SERIM MONITOR for RESIDUAL GLUCOSE

Features	Benefits
Designed for use in the commercial tank cleaning industry	<ul style="list-style-type: none">• Assist wash rack facilities in meeting cleaning guidelines
Ready-to-use strips, simple procedure	<ul style="list-style-type: none">• No calculations or “drop counting” needed• No preparation or mixing of reagents
Quick, qualitative results in 30 to 60 seconds.	<ul style="list-style-type: none">• Simple, quick and reliable method
Simple to interpret color blocks	<ul style="list-style-type: none">• Accurate and consistent results minimize variation between readers• Color of indicator pad is directly compared to color blocks on bottle label
Consistent color reactions	<ul style="list-style-type: none">• Results not affected by aging during the shelf life of the product
Each bottle clearly labeled with: <ul style="list-style-type: none">• Lot number• Expiration date	<ul style="list-style-type: none">• Traceability of product from manufacturing to final user• Leaves no doubt as to the age or integrity of the product

References:

1. CRA Sweetener Terminal and Wash Guidelines, July 2012. Corn Refiners Association, Washington, DC 20006.
2. Model Tanker Wash Guidelines for the Fruit Juice Industry, April 2013. Juice Products Association, Washington, DC 20005.
3. Guidance on Bulk Transport of Juice Concentrates and Certain Shelf Stable Juices. U.S. Department of Health and Human Services, Food and Drug Administration, Center for Food Safety and Applied Nutrition, April 24, 2003.



Serim Research Corporation

P.O. Box 4002, Elkhart, IN 46514-0002
Phone: (800) 542-4670 ■ (574)264-3440 ■ FAX (574)266-6222
E-mail: customerservice@serim.com ■ Website: www.serim.com

Certified to ISO 9001:2008 & ISO 13485:2003