

SensoDirect Oxi200 (IP 67 waterproof)



The microprocessor-controlled SensoDirect Oxi 200 handheld meter from Lovibond® meets the day-to-day demands for sturdy and reliable system for the measurement of temperature and dissolved oxygen.

The water-tight housing complies with **IP67** and is equipped as standard with protective armouring and built-in electrode holder ensuring reliable operation even in extreme ambient conditions.

The support can be flipped up to hang the meter on pipes or branches.

A direct, easily understood user interface, outlining the required configuration options for all three systems, facilitates meter operation both outdoors and in the laboratory.

The automatic Hold function "freezes" stable measuring data in the display and indicates the presence of stable and reproducible results.

The internal memory allows storage of 20 data sets to facilitate subsequent evaluation.

The integral automatic switch-off feature, varying from 1 to 120 minutes, increases the operating life of the units.

The power consumption of all three units has been reduced to a minimum. As a result, the 4 x 1.5 V integrated batteries have an operating life of up to 12,000 hours, depending on the unit version.

The galvanic, membrane-covered oxygen sensor with built-in temperature sensor allows instant measurement without the need for time-consuming polarisation.

Determination of Oxygen Temperature

Oxi200

- Dissolved Oxygen (O₂)
- O₂ Concentration in mg/l
- O₂ Saturation in %
- °C/°F

Applications

- Drinking Water
- Cooling/Boiler Water
- Waste Water
- Pool Water
- Surface Water
- Water Treatment Companies
- Industrial and Governmental Laboratories

Technical Data

O₂ partial pressure	0.0...570.0 hPa, 0...1200 hPa 0.0...427.5 mm Hg, 0...900 mm Hg
O₂ concentration	0.00...25.00 mg/L, 0.0...70.0 mg/L
O₂ saturation	0.0...250.0 %, 0...600 %
Accuracy	± 1.5% ± 0.2 mg/L (0...25 mg/L) ± 2.5% ± 0.3 mg/L (25...70 mg/L) ± 1 Digit
Temperature	-5.0 ... + 50.0 °C 23.0 ... 122.0 ° F
Accuracy	± 0.1 °C
Abs. air pressure	500..1100 hPa
Accuracy	± 0.5% full scale
Nominal temperature	25 °C
Operating temperature	0 to +50 °C
Storage temperature	-20 to +70 °C
Power supply	4 x 1.5 V battery, Type AA Operating time up to 12.000 h
Power consumption	max. 0.25 mA
Auto-Off function	0 - 120 minutes
Dimensions	175 x 140 x 45 mm (L x W x H)
Weight	approx. 580 g
Electrode	Self-polarising oxygen electrode with integrated NTC sensor Connection: 7-pin DIN socket Installation diameter: 12.0 ± 0.2 mm Overall length: approx. 220 mm (incl. kink protection) Operating temperature: 0...40 °C

CE-Conformity

Accessories

Code	Article
723201	Oxygen sensor, 1.5 m cable
723210	Oxygen sensor, 10 m cable
723230	Oxygen sensor, 30 m cable
723250	Service Set Oxygen sensor 3 interchangeable membrane heads, 100 ml plastic bottle KOH-solution 3 mol/l
723260	Protection cap for depth measurement
725020	Case with foam inlet



SensoDirect Oxi200 in case

Features

- Oxygen partial pressure, Oxygen concentration, Oxygen saturation, Temperature measurement
- Automatic absolute air pressure measurement
- Auto Hold function
- Easy calibration against oxygen in air
- Salinity correction
- Self-polarising galvanic oxygen probe, allows instant measurement after the system is switched on
- Low battery and battery change indicator
- Sensor evaluation in the display
- Accessories for depth measurement
- Battery operation period up to 12000 hours
- Shock-absorbing rubber protective armouring
- Waterproof

Delivery Content

Order Code: 723220
SensoDirect Oxi200
 with batteries,
 oxygen sensor (1.5 m cable),
 electrolyte (KOH), 3 interchangeable
 membrane heads, in case, manual,
 warranty information

Order Code: 723221
SensoDirect Oxi200
 as above, but with
 oxygen sensor 10 m cable

Order Code: 723222
SensoDirect Oxi200
 as above, but with
 oxygen sensor 30 m cable