

How to Order Custom pH Cables


Instructions: Complete this part number by selecting from options (Step1-4) and filling in the boxes.





STEP 1

Choose Electrode Plug









STEP 2

Choose Cable Type

Type A 3 mm, low noise, shielded coaxial cable is lightweight and very flexible. The 3 mm cable is frequently chosen for benchtop installations where space is at a premium and cables are required to make many sharp turns and twists.

Type M 5 mm, low noise, shielded coaxial cable is thicker and more rugged. The 5 mm cable is often specified for pilot and process installations.

Type N 5 mm, low noise, shielded coaxial cable is jacketed with an extra lead for connecting solution ground to differential input style transmitters.

Type Z

6 mm, low noise, shielded triaxial cable is jacketed with an
extra lead for connecting solution ground to differential input
style transmitters.

STEP 3Choose Cable Length

0 3 FT (1 M)

6

1 0 10 FT (3M)

Specify length

STEP 4

Choose Instrument Connector


























Crimped Ferrules with a Solution Ground Lead

STEP 5

Call, fax or send an e-mail, with the completed part number, and receive pricing and delivery information. If you need any other assistance, please feel free to contact us.

6 FT (2 M)



Measurement and Control Products for Science and Industry

19 Thomas, Irvine, California 92618 USA

Phone: (949) 829-5555 **Toll-Free:** (800) 288-2833 **Fax:** (949) 829-5560 **E-Mail:** sales@broadleyjames.com **Website:** www.broadleyjames.com