

## TC-2, TC-3 CONDUCTIVITY TESTER

- Easy to use, range depends on model
- Conductivity and temperature value displayed simultaneously.
- Splash-proof, pocket-size housing, possible to use during rain.
- Fast stabilisation of the readout.
- Stainless steel, unreplaceable electrodes.
- Automatic temperature compensation ( $\alpha = 2\%/^{\circ}\text{C}$ ).
- Calibration in standard solution.
- Price lower than standard conductivity cell cost.
- 12-month warranty.



Model	TC-2	TC-3
Range	0 + 1800 uS/cm	0 + 19.99 mS/cm
Resolution	1 uS/cm	0.01 mS/cm
Accuracy	±2% of the range	±2% of the range
Temperature measurement range	-50 ÷ 70 °C	-50 ÷ 70 °C
Temperature measurement accuracy	±1 °C	±1 °C
Automatic temperature compensation	0 ÷ 50 °C	0 ÷ 50 °C
Elektrodes	Steel	Steel
Power supply	4 x 1.5 V (LR44)	4 x 1.5 V (LR44)
Dimensions (mm)	170 x 36 x 23	170 x 36 x 23

**ELMETRON**<sup>®</sup> Sp. j.  
41-814 Zabrze ul. Witosa 10 POLAND  
tel. +48 32 2738106 fax +48 32 2738114  
[www.elmetron.pl](http://www.elmetron.pl) e-mail: [info@elmetron.com.pl](mailto:info@elmetron.com.pl)