

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.12.2017

Version number 14

Revision: 01.12.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name: **COD / CSB 0-1500 mg/l**

Catalog number: 424434, 2420721, 420721, 2420726, 420726

1.2 Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / the preparation: Reagent for water analysis

1.3 Details of the supplier of the safety data sheet

Supplier:

Tintometer GmbH
Schleefstraße 8-12
44287 Dortmund
Made in Germany
www.lovibond.com

phone: +49 231 94510-0
e-mail: sales@tintometer.de

Tintometer GmbH
Division AQUALYTIC®
Schleefstr. 12
44287 Dortmund
Made in Germany
www.aqualytic.de

phone: +49 231 94510-755
e-mail: sales@aqualytic.de

The Tintometer Limited
Lovibond® House
Sun Rise Way
Amesbury
Wiltshire SP4 7GR
United Kingdom

phone : +44 1980 664800
e-mail: SDS@tintometer.com

Informing department:

e-mail: produktsicherheit@tintometer.de
Product Safety Department

1.4 Emergency telephone number:

Poison Center Berlin, Germany
phone: 0049 30 30686 790
Languages: English and German

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS06 skull and crossbones

Acute Tox. 3 H311 Toxic in contact with skin.



GHS08 health hazard

Muta. 1B H340 May cause genetic defects.

Carc. 1B H350 May cause cancer.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS05 corrosion

(Contd. on page 2)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.12.2017

Version number 14

Revision: 01.12.2017

Product name: COD / CSB 0-1500 mg/l

(Contd. of page 1)

Met. Corr.1 H290 May be corrosive to metals.
 Skin Corr. 1A H314 Causes severe skin burns and eye damage.
 Eye Dam. 1 H318 Causes serious eye damage.



GHS09 environment

Aquatic Acute 1 H400 Very toxic to aquatic life.
 Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

2.2 Label elements

· **Labelling according to Regulation (EC) No 1272/2008** The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



GHS05



GHS06



GHS08



GHS09

· **Signal word** Danger

· Hazard-determining components of labelling:

sulphuric acid 82 %
 mercury sulphate
 potassium dichromate

· Hazard statements

H290 May be corrosive to metals.
 H302 Harmful if swallowed.
 H311 Toxic in contact with skin.
 H314 Causes severe skin burns and eye damage.
 H340 May cause genetic defects.
 H350 May cause cancer.
 H373 May cause damage to organs through prolonged or repeated exposure.
 H410 Very toxic to aquatic life with long lasting effects.

· Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308+P310 IF exposed or concerned: Immediately call a POISON CENTER/doctor.
 P405 Store locked up.

· Additional information:

EUH208 Contains potassium dichromate. May produce an allergic reaction.
 Restricted to professional users.

· 2.3 Other hazards

Contact with skin and inhalation of aerosols/ vapours of the preparation should be avoided.
 Acid burns have to be treated immediately, as it may otherwise cause badly curing wounds.
 CAS 7783-35-9: Danger by skin resorption.

· Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be persistent, bioaccumulative and toxic (PBT) or very persistent and very bioaccumulative (vPvB), according to the criteria given in Annex XIII of Regulation (EC) No. 1907/2006.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· **Description:** sulfuric acid solution

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.12.2017

Version number 14

Revision: 01.12.2017

Product name: COD / CSB 0-1500 mg/l

(Contd. of page 2)

Dangerous components:

The percent content of the chromium compound mentioned below refers to the amount of chromate ions dissolved in water.
The percent content of the mercury compound mentioned below refers to the amount of the pure mercury therein.

CAS: 7664-93-9 EINECS: 231-639-5 Index No: 016-020-00-8 Reg.nr.: 01-2119458838-20-XXXX	sulphuric acid ☞ Met. Corr. 1, H290; Skin Corr. 1A, H314	80–90%
CAS: 7783-35-9 EINECS: 231-992-5 Index No: 080-002-00-6	mercury sulphate ☞ Acute Tox. 2, H300; Acute Tox. 1, H310; Acute Tox. 2, H330; ☞ STOT RE 2, H373; ☞ Aquatic Acute 1, H400; Aquatic Chronic 1, H410	0.25–1%
CAS: 10294-26-5 EINECS: 233-653-7	disilver(1+) sulphate ☞ Eye Dam. 1, H318; ☞ Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100)	0.25–1%
CAS: 7778-50-9 EINECS: 231-906-6 Index No: 024-002-00-6 Reg.nr.: 01-2119454792-32-XXXX	potassium dichromate ☞ Ox. Sol. 2, H272; ☞ Acute Tox. 3, H301; Acute Tox. 2, H330; ☞ Resp. Sens. 1, H334; Muta. 1B, H340; Carc. 1B, H350; Repr. 1B, H360FD; STOT RE 1, H372; ☞ Skin Corr. 1B, H314; ☞ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ☞ Acute Tox. 4, H312; Skin Sens. 1, H317	0.25–1%

SVHC

CAS: 7778-50-9 | potassium dichromate

Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures
General information

Personal protection for the First Aider!
Instantly remove any clothing soiled by the product.

After inhalation

Supply fresh air or oxygen; call for doctor.
In case of unconsciousness bring patient into stable side position for transport.

After skin contact

Wash with polyethylene glycol 400 and then rinse with copious amounts of water.
Immediate medical treatment necessary. Failure to treat burns can prevent wounds from healing.

After eye contact

Rinse opened eye for several minutes (at least 15 min) under running water. Then consult doctor.
Call a doctor immediately.

After swallowing

Rinse out mouth and then drink 1-2 glasses of water.
Do not induce vomiting; instantly call for medical help.

4.2 Most important symptoms and effects, both acute and delayed:

burns
absorption
after inhalation:
breathing difficulty
coughing
asthma attacks
damage to the affected mucous membranes
after swallowing:
metallic taste
bloody diarrhoea
pain
strong caustic effect.
unconsciousness
methaemoglobin formation
sickness
vomiting
cramps

Danger
Danger of system failure.
Danger of gastric perforation.
Danger of pulmonary oedema.

(Contd. on page 4)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.12.2017

Version number 14

Revision: 01.12.2017

Product name: COD / CSB 0-1500 mg/l

(Contd. of page 3)

4.3 Indication of any immediate medical attention and special treatment needed:

If swallowed or in case of vomiting, danger of entering the lungs
Subsequent observation for pneumonia and pulmonary oedema

SECTION 5: Firefighting measures

5.1 Extinguishing media

· **Suitable extinguishing agents** CO₂, sand, extinguishing powder.

· **For safety reasons unsuitable extinguishing agents** Water.

5.2 Special hazards arising from the substance or mixture

The product is not combustible.

Formation of toxic gases is possible during heating or in case of fire.

Can be released in case of fire:

Sulphur oxides (SO_x)

mercury vapours

chromium trioxide

Dipotassium oxide

5.3 Advice for firefighters
Protective equipment:

Wear self-contained breathing apparatus.

Wear full protective suit.

Additional information

Collect contaminated fire fighting water separately. It must not enter drains.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Ambient fire may liberate hazardous vapours.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures
Advice for non-emergency personnel:

Wear protective equipment. Keep unprotected persons away.

Avoid substance contact.

Ensure adequate ventilation

Use breathing protection against the effects of fumes/dust/aerosol.

· **Advice for emergency responders:** Protective equipment: see section 8

6.2 Environmental precautions:

Do not allow product to reach sewage system or water bodies.

Inform respective authorities in case product reaches water or sewage system.

6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Use neutralising agent.

Neutralize with diluted sodium hydroxide solution.

Absorb with liquid-binding material (sand, diatomite, universal binders).

Dispose of contaminated material as waste according to item 13.

6.4 Reference to other sections

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

7.1 Precautions for safe handling
Advice on safe handling:

Open and handle container with care.

Work only in fume cupboard.

Prevent formation of aerosols.

Hygiene measures:

Do not inhale gases / fumes / aerosols.

Do not get in eyes, on skin, or on clothing.

Take off immediately all contaminated clothing.

Store protective clothing separately.

Wash hands during breaks and at the end of the work.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.12.2017

Version number 14

Revision: 01.12.2017

Product name: COD / CSB 0-1500 mg/l

(Contd. of page 4)

Do not eat, drink or smoke when using this product.

7.2 Conditions for safe storage, including any incompatibilities
Storage
Requirements to be met by storerooms and containers: Store in cool location.

Information about storage in one common storage facility:

Store away from metals.

Do not store together with alkalis (caustic solutions).

Store away from flammable substances.

Further information about storage conditions:

Store in a locked cabinet or with access restricted to technical experts or their assistants.

Store in cool, dry conditions in well sealed containers.

Protect from heat and direct sunlight.

Protect from the effects of light.

Protect from humidity and keep away from water.

This product is hygroscopic.

Store under dry conditions.

Recommended storage temperature: 20°C +/- 5°C

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters
Components with limit values that require monitoring at the workplace:
CAS: 7664-93-9 sulphuric acid

WEL (Great Britain)	Long-term value: 0.05* mg/m ³ *mist: defined as thoracic fraction
---------------------	---

IOELV (European Union)	Long-term value: 0.05 mg/m ³
------------------------	---

OEL (Sweden)	Short-term value: 0.2 mg/m ³ Long-term value: 0.1 mg/m ³ C, V
--------------	---

CAS: 7783-35-9 mercury sulphate

WEL (Great Britain)	Long-term value: 0.02 mg/m ³ as Hg
---------------------	--

IOELV (European Union)	Long-term value: 0.02 mg/m ³ as Hg
------------------------	--

OEL (Sweden)	Long-term value: 0.02 mg/m ³ inhalerbart damm, som Hg; B
--------------	--

CAS: 10294-26-5 disilver(1+) sulphate

WEL (Great Britain)	Long-term value: 0.01 mg/m ³ as Ag
---------------------	--

OEL (Sweden)	Long-term value: 0.1 mg/m ³ som Ag, totaldamm
--------------	---

CAS: 7778-50-9 potassium dichromate

WEL (Great Britain)	Long-term value: 0.05 mg/m ³ as Cr; Carc, Sen, BMGV
---------------------	---

OEL (Sweden)	Short-term value: 0.015 mg/m ³ Long-term value: 0.005 mg/m ³ totaldamm; C,S,V; som Cr;
--------------	--

Regulatory information

WEL (Great Britain): EH40/2011

IOELV (European Union): (EU) 2017/164

OEL (Sweden): AFS2015:7

Additional information: IOELV = Indicative Occupational Exposure Limit

DNELs

Derived No Effect Level (DNEL)

CAS: 7664-93-9 sulphuric acid

Inhalative	DNEL	0.1 mg/m ³ (Worker / acute / local effects)
------------	------	--

		0.05 mg/m ³ (Worker / acute / systemic effects)
--	--	--

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.12.2017

Version number 14

Revision: 01.12.2017

Product name: COD / CSB 0-1500 mg/l

(Contd. of page 5)

Recommended monitoring procedures:

Methods for measurement of the workplace atmosphere have to correspond to the requirements of norms DIN EN 482 and DIN EN 689.

PNECs

Predicted No Effect Concentration (PNEC)

CAS: 7664-93-9 sulphuric acid	
PNEC	8.8 mg/l (Sewage treatment plant)
	0.00025 mg/l (Marine water)
	0.0025 mg/l (Fresh water)
PNEC	0.002 mg/kg (Marine sediment)
	0.002 mg/kg (Fresh water sediment)

Ingredients with biological limit values:

CAS: 7783-35-9 mercury sulphate	
BMGV (Great Britain)	20 µmol/mol creatinine
	Medium: urine
	Sampling time: random
	Parameter: mercury
CAS: 7778-50-9 potassium dichromate	
BMGV (Great Britain)	10 µmol/mol creatinine
	Medium: urine
	Sampling time: post shift
	Parameter: chromium

Regulatory information BMGV (Great Britain): EH40/2011

Additional information: The lists that were valid during the compilation were used as basis.

8.2 Exposure controls
Engineering measures:

Technical measures and appropriate working operations should be given priority over the use of personal protective equipment. See item 7.

Personal protective equipment
Breathing equipment:

Use breathing protection against the effects of fumes/dust/aerosol.

In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.

Recommended filter device for short term use: Combination filter B-P2

Protection of hands:

Acid resistant gloves

Preventive skin protection by use of skin-protecting agents is recommended.

After use of gloves apply skin-cleaning agents and skin cosmetics.

Material of gloves

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.3 mm

Penetration time of glove material

Value for the permeation: Level = 1 (< 10 min)

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:

Tightly sealed safety glasses.

Face protection

Body protection: Acid resistant protective clothing

Limitation and supervision of exposure into the environment:

Avoid release to the environment.

Do not allow product to reach sewage system or water bodies.

* SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties
Appearance:

Form / Physical state: Liquid

(Contd. on page 7)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.12.2017

Version number 14

Revision: 01.12.2017

Product name: COD / CSB 0-1500 mg/l

(Contd. of page 6)

· Colour:	Yellow-brown
· Odour:	Recognisable
· Odour threshold:	Not determined.
· pH-value at 20 °C:	1
· Melting point/Freezing point:	Not determined
· Initial boiling point and boiling range:	> 100 °C
· Flash point:	Not applicable
· Flammability (solid, gas):	Not applicable.
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not self-igniting.
· Explosive properties:	Product is not explosive.
· Flammability or explosive limits:	
· Lower:	Not applicable
· Upper:	Not applicable
· Oxidising properties:	CAS 7664-93-9 : Oxidising potential
· Vapour pressure:	Not determined.
· Density at 20 °C:	1,76 g/cm ³
· Relative density:	Not determined.
· Vapour density:	Not determined.
· Evaporation rate:	Not determined.
· Solubility(ies):	
· Water:	Fully miscible
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	Not determined.
· Solvent content:	
· Organic solvents:	0,0 %
· Water:	< 20 %
· Solids content:	< 5 %
· 9.2 Other information	No further relevant information available.

* SECTION 10: Stability and reactivity

- **10.1 Reactivity** see section 10.3
- **10.2 Chemical stability** Stable at ambient temperature (room temperature).
- **10.3 Possibility of hazardous reactions**
 - Corrosive action on metals
 - Reacts with metals forming hydrogen (--> Explosive!)
 - When diluting, always add acid to water, never vice versa
 - Diluting or dissolving in water always causes rapid heating
 - Reacts with reducing agents
 - Reacts with acids, alkalis and oxidizing agents
 - Reacts with peroxides
 - Reacts with halogenated compounds
 - Reacts with ammonia (NH₃).
- **10.4 Conditions to avoid** strong heating
- **10.5 Incompatible materials:**
 - metals
 - organic substances
 - combustible substances
 - organic solvents
- **10.6 Hazardous decomposition products:** see section 5

GB
(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.12.2017

Version number 14

Revision: 01.12.2017

Product name: COD / CSB 0-1500 mg/l

(Contd. of page 7)

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Classification according to calculation procedure:

Harmful if swallowed.

Toxic in contact with skin.

Acute toxicity estimate (ATE_(MIX)) - Calculation method:

Oral	CLP ATE _(MIX)	681 mg/kg (.)
Dermal	CLP ATE _(MIX)	694 mg/kg (.)
Inhalative	CLP ATE _(MIX)	5.9 mg/l/4h (aerosol)

LD/LC50 values that are relevant for classification:

CAS: 7664-93-9 sulphuric acid

Oral	LD50	2140 mg/kg (rat) (IUCLID)
	LC 50	510 mg/m ³ /2h (rat) IUCLID

CAS: 7783-35-9 mercury sulphate

Oral	LD50	5 mg/kg (ATE)
	LD50.	57 mg/kg (rat) (RTECS)
Dermal	LD50	5 mg/kg (ATE)
	LD50.	625 mg/kg (rat)
Inhalative	LC50	0.05 mg/l/4h (ATE)

CAS: 10294-26-5 disilver(1+) sulphate

Oral	LD50	>5000 mg/kg (rat) (OECD 401) (Registrant, ECHA)
------	------	--

CAS: 7778-50-9 potassium dichromate

Oral	LD50	90.5 mg/kg (rat) (OECD 401) (ECHA, registrant: LD50 = 90.5 mg/kg female to 168.0 mg/kg male)
	LDLo	26 mg/kg (child) 143 mg/kg (man)
	Dermal	LD50
Inhalative	LC50	0.094 mg/l/4h (rat) (OECD 403, Aerosol)
	LD50 IPR	28 mg/kg (rat)

Primary irritant effect:

Skin corrosion/irritation

Causes severe skin burns and eye damage.

Serious eye damage/irritation

Causes serious eye damage.

Risk of blindness!

Information on components:

CAS: 10294-26-5 disilver(1+) sulphate

Irritation of skin	OECD 404	(rabbit: no irritation)
Irritation of eyes	OECD 405	(rabbit: burns)

CAS: 7778-50-9 potassium dichromate

Irritation of skin	OECD 404	(rabbit: irritation)
--------------------	----------	----------------------

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Information on components:

CAS 7783-35-9: Sensitizing effect by skin contact is possible by prolonged/repeated exposure.

CAS 7778-50-9: Sensitizing effect by inhalation and skin contact is possible by prolonged exposure.

CAS: 7778-50-9 potassium dichromate

Sensitisation	Patch test (human)	(positive) (IUCLID)
---------------	--------------------	------------------------

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction) The following statements refer to the mixture:

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.12.2017

Version number 14

Revision: 01.12.2017

Product name: COD / CSB 0-1500 mg/l

(Contd. of page 8)

- **Germ cell mutagenicity**
May cause genetic defects.
- **Carcinogenicity**
May cause cancer.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT (specific target organ toxicity) -single exposure** Based on available data, the classification criteria are not met.
- **STOT (specific target organ toxicity) -repeated exposure**
May cause damage to organs through prolonged or repeated exposure.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
Mercury compounds have a cytotoxic and protoplasmatoxic effect.
The principal signs manifest themselves in the CNS.
Inhalable chromium (VI) compounds have clearly shown themselves to be carcinogenic in animal experiments.
Poor tendency for ulcers to heal following penetration of substance into the wound.
Lethal dose (man): 0.5 g
Antidotes: chelating agents such as EDTA, DMPS
Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.
The aerosol is corrosive to the eyes, the skin and the respiratory tract. Inhalation of aerosols may cause lung oedema.
Sulfuric acid: erosion of the teeth, cancer
- **Experience with humans:**
CAS 7778-50-9: Can cause liver damages.
CAS 7778-50-9: Can cause kidney damages.
CAS 7778-50-9: May cause lung damages.
CAS 7778-50-9: Can cause cardiac damages.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

CAS: 7664-93-9 sulphuric acid	
EC50	>100 mg/l/48h (Daphnia magna) (OECD 202) (ECHA)
LC50	16–29 mg/l/96h (bluegill) (Merck)
CAS: 7783-35-9 mercury sulphate	
LC50	0.5 mg/l/48h (gold orfe)
EC50	0.005–3.6 mg/l/48h (Daphnia magna)
LC50	0.19 mg/l/96h (fathhead minnow)
CAS: 10294-26-5 disilver(1+) sulphate	
EC50	0.0045 mg/l/48h (Daphnia magna) (GESTIS)
EC50	0.0049 mg/l/96h (fathhead minnow)
EC10	0.00214 mg/l (Daphnia magna) (ASTM) (21d, test substance: AgNO ₃)
	0.00039 mg/l (fathhead minnow) (ASTM E1241-98) (28d, test substance: AgNO ₃ , result in mg/l Ag)
CAS: 7778-50-9 potassium dichromate	
EC50	0.62 mg/l/48h (Daphnia magna) (OECD 202) (Merck)
NOEC	0.016–0.064 mg/l (Daphnia magna) (7d)
	6 mg/l (fathhead minnow) (7d)
IC50	0.16–0.59 mg/l/96 h (Chlorella vulgaris) (IUCRID)
EC50	0.31 mg/l/72 h (Desmodemus subspicatus)
LC50	58.5 mg/l/96h (byr)
	0.131 mg/l/96h (bluegill)
	160 mg/l/96h (guppy)

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.12.2017

Version number 14

Revision: 01.12.2017

Product name: COD / CSB 0-1500 mg/l

(Contd. of page 9)

	26.13 mg/l/96h (fathead minnow) (Merck/IUCLID)
--	---

Bacterial toxicity:
CAS: 7778-50-9 potassium dichromate
EC50 58 mg/l (Photobacterium phosphoreum) (30 min; Microtox-Test)

Other information:

Toxic for fish:

sulphates > 7 g/l

12.2 Persistence and degradability .
Other information:

Mixture of inorganic compounds.

Methods for the determination of biodegradability are not applicable to inorganic substances.

12.3 Bioaccumulative potential

BCF = Bioconcentration factor

CAS: 10294-26-5 disilver(1+) sulphate

BCF	2.5 (rainbow trout) (8d, 15°C, test substance: AgNO ₃)
------------	---

CAS: 7778-50-9 potassium dichromate

BCF	17.4 (rainbow trout)
------------	----------------------

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be persistent, bioaccumulative and toxic (PBT) or very persistent and very bioaccumulative (vPvB), according to the criteria given in Annex XIII of Regulation (EC) No. 1907/2006.

12.6 Other adverse effects

Forms corrosive mixtures with water even if diluted.

Harmful effect due to pH shift.

Avoid transfer into the environment.

Water hazard:

Do not allow product to reach ground water, water bodies or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into soil.

SECTION 13: Disposal considerations

13.1 Waste treatment methods
Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to disposers of hazardous waste.

European waste catalogue

16 05 07*	discarded inorganic chemicals consisting of or containing hazardous substances
-----------	--

Uncleaned packagings:
Recommendation: Disposal must be made according to official regulations.

Recommended cleaning agent: Water, if necessary with cleaning agent.

SECTION 14: Transport information

14.1 UN-Number
ADR, IMDG, IATA

UN2922

14.2 UN proper shipping name
ADR

2922 CORROSIVE LIQUID, TOXIC, N.O.S. (SULPHURIC ACID, MERCURY SULPHATE), ENVIRONMENTALLY HAZARDOUS CORROSIVE LIQUID, TOXIC, N.O.S. (SULPHURIC ACID, MERCURY SULPHATE), MARINE POLLUTANT

IMDG
IATA

CORROSIVE LIQUID, TOXIC, N.O.S. (SULPHURIC ACID, MERCURY SULPHATE)

(Contd. on page 11)

GB

Safety data sheet

according to 1907/2006/EC, Article 31




Printing date 01.12.2017

Version number 14

Revision: 01.12.2017

Product name: COD / CSB 0-1500 mg/l

(Contd. of page 10)

<ul style="list-style-type: none"> · 14.3 Transport hazard class(es) · ADR 	
	
<ul style="list-style-type: none"> · Class · Label 	8 (CT1) Corrosive substances. 8+6.1
<ul style="list-style-type: none"> · IMDG 	
	
<ul style="list-style-type: none"> · Class · Label 	8 Corrosive substances. 8/6.1
<ul style="list-style-type: none"> · IATA 	
	
<ul style="list-style-type: none"> · Class · Label 	8 Corrosive substances. 8 (6.1)
<ul style="list-style-type: none"> · 14.4 Packing group · ADR, IMDG, IATA 	
	II
<ul style="list-style-type: none"> · 14.5 Environmental hazards: · Marine pollutant: · Special marking (ADR): 	
	Yes Symbol (fish and tree) Symbol (fish and tree)
<ul style="list-style-type: none"> · 14.6 Special precautions for user · Kemler Number: · EMS Number: · Segregation groups · Stowage Category · Stowage Code 	
	Warning: Corrosive substances. 86 F-A,S-B Acids B SW2 Clear of living quarters.
<ul style="list-style-type: none"> · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code 	
	Not applicable.
<ul style="list-style-type: none"> · Transport/Additional information: 	
<ul style="list-style-type: none"> · ADR · Limited quantities (LQ) · Excepted quantities (EQ) 	
	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
<ul style="list-style-type: none"> · Transport category · Tunnel restriction code 	2 E
<ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) 	
	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.12.2017

Version number 14

Revision: 01.12.2017

Product name: COD / CSB 0-1500 mg/l

(Contd. of page 11)

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 689/2008 concerning the export and import of dangerous chemicals:

None of the ingredients is listed.

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer:

None of the ingredients is listed.

Directive 2012/18/EU (SEVESO III):

- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category** E1 Hazardous to the Aquatic Environment
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 100 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 200 t

LIST OF SUBSTANCES SUBJECT TO AUTHORISATION (ANNEX XIV)

CAS: 7778-50-9 | potassium dichromate

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 18, 28, 47

Information about limitation of use:

Observe employment restrictions for pregnant and nursing mothers according to the 'mother protection guideline' (92/85/EEC). Employment restrictions concerning young persons must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H272 May intensify fire; oxidiser.
- H290 May be corrosive to metals.
- H300 Fatal if swallowed.
- H301 Toxic if swallowed.
- H310 Fatal in contact with skin.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H330 Fatal if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H340 May cause genetic defects.
- H350 May cause cancer.
- H360FD May damage fertility. May damage the unborn child.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

Training hints Provide adequate information, instruction and training for operators.

Abbreviations and acronyms:

- EC50: effective concentration, 50 percent (in vivo)
- OECD: Organisation for Economic Co-operation and Development
- STOT: specific target organ toxicity
 - SE: single exposure
 - RE: repeated exposure
- EC50: half maximal effective concentration
- IC50: half maximal inhibitory concentration
- NOEL or NOEC: No Observed Effect Level or Concentration
- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- DNEL: Derived No-Effect Level (REACH)

(Contd. on page 13)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.12.2017

Version number 14

Revision: 01.12.2017

Product name: COD / CSB 0-1500 mg/l

(Contd. of page 12)

PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
SVHC: Substances of Very High Concern
vPvB: very Persistent and very Bioaccumulative
Ox. Sol. 2: Oxidizing solids – Category 2
Met. Corr. 1: Corrosive to metals – Category 1
Acute Tox. 2: Acute toxicity – Category 2
Acute Tox. 3: Acute toxicity – Category 3
Acute Tox. 1: Acute toxicity – Category 1
Acute Tox. 4: Acute toxicity – Category 4
Skin Corr. 1A: Skin corrosion/irritation – Category 1A
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Resp. Sens. 1: Respiratory sensitisation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
Muta. 1B: Germ cell mutagenicity – Category 1B
Carc. 1B: Carcinogenicity – Category 1B
Repr. 1B: Reproductive toxicity – Category 1B
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Sources

Data arise from safety data sheets, reference works and literature.
ECHA: European Chemicals Agency <http://echa.europa.eu>
IUCLID (International Uniform Chemical Information Database)
GESTIS- Stoffdatenbank (Substance Database, Germany)
RTECS (Registry of Toxic Effects of Chemical Substances)

· * Data compared to the previous version altered.