

Simplicity in Water Analysis

Cover Page for Safety Data Sheet

Thank you for choosing CHEMetrics, Inc. We appreciate your business. In order to best serve your needs for accurate and complete Safety Data, we offer the following information as supplemental to the attached SDS.

SDS No.: S9001

Version No.: 2.2

Product Name: Activator Solution for Silica CHEMets®, ULR CHEMets®, and Vacu-vials®

Kits

Part Nos.: A-9001

Product Descriptions:

Activator Solution: Plastic bottle, contains approximately 18 mL of liquid reagent. Test kits contain one (1) bottle of solution. Activator Solution packs contain six (6) bottles of solution.

Addendum to Section 14 Transport Information:

Shipping container markings and labels for this product, as received, may vary from the contents of section 14 of the SDS for one or both of the following reasons:

- CHEMetrics has packaged this product as Dangerous Goods in Excepted Quantities according to IATA, US DOT, and IMDG regulations.
- CHEMetrics has packaged this product as part of a test kit or reagent set composed of various chemical reagents and elected to ship as UN 3316 Chemical Kit, Hazard Class 9, Packing Group II or III.

In case of reshipment, it is the responsibility of the shipper to determine appropriate labels and markings in accordance with applicable transportation regulations.

Additional Information:

- "Print Date" = Revision Date (expressed as DD/MM/YYYY)
- Test kits and reagents sets may contain additional chemical reagents. See separate SDS(s).



Activator Solution for Silica CHEMets, ULR CHEMets, and Vacu-vials Kits

CHEMetrics, Inc.

Chemwatch Hazard Alert Code: 4

Chemwatch: **9-90599** SDS No: **\$9001** Version No: **2.2** Issue Date: 03/09/2014 Print Date: 12/03/2015 Initial Date: 06/09/2014 S.GHS.USA.EN

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

| Product name | Activator Solution for Silica CHEMets, ULR CHEMets, and Vacu-vials Kits | |
|-------------------------------|---|--|
| Synonyms | Part No.: A-9001 | |
| Proper shipping name | Corrosive liquids, n.o.s. (contains sulfuric acid) | |
| Chemical formula | Not Applicable | |
| Other means of identification | Not Available | |
| CAS number | Not Applicable | |

Relevant identified uses of the substance or mixture and uses advised against

| Relevant identified uses | Component of water analysis test kits K-9003, K-9010, K-9011 |
|--------------------------|--|
|--------------------------|--|

Details of the manufacturer/importer

| Registered company name | CHEMetrics, Inc. |
|-------------------------|---|
| Address | 4295 Catlett Road, Midland, VA. 22728 United States |
| Telephone | 1-540-788-9026 |
| Fax | 1-540-788-4856 |
| Website | www.chemetrics.com |
| Email | technical@chemetrics.com |

Emergency telephone number

| Association / Organisation | ChemTel Inc. |
|-----------------------------------|------------------|
| Emergency telephone numbers | 1-800-255-3924 |
| Other emergency telephone numbers | +01-813-248-0585 |

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

GHS Classification

Metal Corrosion Category 1, Skin Corrosion/Irritation Category 1A, Serious Eye Damage Category 1, Skin Sensitizer Category 1, STOT - SE (Resp. Irr.) Category 3, STOT - RE Category 2

Label elements

GHS label elements







SIGNAL WORD

DANGER

Hazard statement(s)

| H290 | May be corrosive to metals |
|------|---|
| H314 | Causes severe skin burns and eye damage |
| H318 | Causes serious eye damage |
| H317 | May cause an allergic skin reaction |
| H335 | May cause respiratory irritation |

Version No: **2.2** Page **2** of **9** Issue Date: **03/09/2014**

Activator Solution for Silica CHEMets, ULR CHEMets, and Vacu-vials Kits

Print Date: 12/03/2015

| H373 May cause damage to organs through prolonged or repeated exposure |
|--|
|--|

Precautionary statement(s) Prevention

| P101 | If medical advice is needed, have product container or label at hand. |
|------|--|
| P102 | Keep out of reach of children. |
| P103 | Read label before use. |
| P260 | Do not breathe dust/fume/gas/mist/vapours/spray. |
| P271 | Use only outdoors or in a well-ventilated area. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
| P234 | Keep only in original container. |
| P272 | Contaminated work clothing should not be allowed out of the workplace. |

Precautionary statement(s) Response

| P301+P330+P331 | IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. | |
|--|--|--|
| P303+P361+P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. | |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. | |
| P310 | Immediately call a POISON CENTER/doctor/physician/first aider | |
| P302+P352 IF ON SKIN: Wash with plenty of water and soap | | |

Precautionary statement(s) Storage

| P405 | Store locked up. | |
|-----------|--|--|
| P403+P233 | Store in a well-ventilated place. Keep container tightly closed. | |

Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised chemical landfill or if organic to high temperature incineration

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Observe the patient carefully.

Substances

See section below for composition of Mixtures

Mixtures

| CAS No | %[weight] | Name |
|------------|-----------|-------------------------|
| 7732-18-5 | 65 | <u>water</u> |
| 7664-93-9 | 23 | sulfuric acid |
| 12027-67-7 | 12 | ammonium heptamolybdate |

SECTION 4 FIRST AID MEASURES

Description of first aid measures

| Description of first aid measures | | |
|-----------------------------------|---|--|
| Eye Contact | If this product comes in contact with the eyes: Immediately hold eyelids apart and flush the eye continuously with running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. | |
| Skin Contact | If skin or hair contact occurs: Immediately flush body and clothes with large amounts of water, using safety shower if available. Quickly remove all contaminated clothing, including footwear. Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre. Transport to hospital, or doctor. | |
| Inhalation | If furnes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor, without delay. Inhalation of vapours or aerosols (mists, furnes) may cause lung oedema. Corrosive substances may cause lung damage (e.g. lung oedema, fluid in the lungs). As this reaction may be delayed up to 24 hours after exposure, affected individuals need complete rest (preferably in semi-recumbent posture) and must be kept under medical observation even if no symptoms are (yet) manifested. Before any such manifestation, the administration of a spray containing a dexamethasone derivative or beclomethasone derivative may be considered. This must definitely be left to a doctor or person authorised by him/her. (ICSC13719) | |
| Ingestion | For advice, contact a Poisons Information Centre or a doctor at once. Urgent hospital treatment is likely to be needed. If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. | |

Version No: 2.2 Page 3 of 9 Issue Date: 03/09/2014

Activator Solution for Silica CHEMets, ULR CHEMets, and Vacu-vials Kits

Print Date: 12/03/2015

- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- Transport to hospital or doctor without delay.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

For acute or short term repeated exposures to strong acids:

- Airway problems may arise from laryngeal edema and inhalation exposure. Treat with 100% oxygen initially.
- Respiratory distress may require cricothyroidotomy if endotracheal intubation is contraindicated by excessive swelling
- Intravenous lines should be established immediately in all cases where there is evidence of circulatory compromise.
- Strong acids produce a coagulation necrosis characterised by formation of a coagulum (eschar) as a result of the dessicating action of the acid on proteins in specific tissues.
- ▶ Immediate dilution (milk or water) within 30 minutes post ingestion is recommended.
- ▶ **DO NOT** attempt to neutralise the acid since exothermic reaction may extend the corrosive injury
- Be careful to avoid further vomit since re-exposure of the mucosa to the acid is harmful. Limit fluids to one or two glasses in an adult.
- Charcoal has no place in acid management.
- ▶ Some authors suggest the use of lavage within 1 hour of ingestion.

SKIN:

- Skin lesions require copious saline irrigation. Treat chemical burns as thermal burns with non-adherent gauze and wrapping.
- Deep second-degree burns may benefit from topical silver sulfadiazine.

EYE

- Eye injuries require retraction of the eyelids to ensure thorough irrigation of the conjuctival cul-de-sacs. Irrigation should last at least 20-30 minutes. DO NOT use neutralising agents or any other additives. Several litres of saline are required.
- Cycloplegic drops, (1% cyclopentolate for short-term use or 5% homatropine for longer term use) antibiotic drops, vasoconstrictive agents or artificial tears may be indicated dependent on the
- ▶ Steroid eye drops should only be administered with the approval of a consulting ophthalmologist).

[Ellenhorn and Barceloux: Medical Toxicology]

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

- Water spray or fog.
- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

Special hazards arising from the substrate or mixture

Fire Incompatibility

None known.

Advice for firefighters

Fire Fighting

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus.
- Prevent, by any means available, spillage from entering drains or water course
- Use fire fighting procedures suitable for surrounding area.
- Do not approach containers suspected to be hot.

Fire/Explosion Hazard

- Non combustible. Not considered to be a significant fire risk.
- Acids may react with metals to produce hydrogen, a highly flammable and explosive gas.
- Heating may cause expansion or decomposition leading to violent rupture of containers.
- May emit corrosive, poisonous fumes

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Minor Spills

- ▶ Drains for storage or use areas should have retention basins for pH adjustments and dilution of spills before discharge or disposal of material.
- Check regularly for spills and leaks.
- - Clean up all spills immediately. Avoid breathing vapours and contact with skin and eves.
- ▶ Control personal contact with the substance, by using protective equipment.

Major Spills

- ▶ Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus
- Prevent, by any means available, spillage from entering drains or water course
- ▶ Consider evacuation (or protect in place).

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- ▶ Use in a well-ventilated area.
- WARNING: To avoid violent reaction, ALWAYS add material to water and NEVER water to material.
- · Avoid smoking, naked lights or ignition sources.

Version No: **2.2** Page **4** of **9** Issue Date: **03/09/2014**

Activator Solution for Silica CHEMets, ULR CHEMets, and Vacu-vials Kits

For optimum analytical performance, store in the dark and at room temperature.

Wear impact- and splash-resistant eyewear.

Store in original containers.
Keep containers securely sealed.
Store in a cool, dry, well-ventilated area.
Store away from incompatible materials and foodstuff containers.
Protect containers against physical damage and check regularly for leaks.

Conditions for safe storage, including any incompatibilities

| Conditions for safe storage, including any incompatibilities | | |
|--|--|--|
| Suitable container | DO NOT use aluminium or galvanised containers Check regularly for spills and leaks Lined metal can, lined metal pail/ can. Plastic pail. Polyliner drum. Packing as recommended by manufacturer. Check all containers are clearly labelled and free from leaks. | |
| Storage incompatibility | Inorganic acids are generally soluble in water with the release of hydrogen ions. The resulting solutions have pH's of less than 7.0. Inorganic acids neutralise chemical bases (for example: amines and inorganic hydroxides) to form salts - neutralisation can generate dangerously large amounts of heat in small spaces. The dissolution of inorganic acids in water or the dilution of their concentrated solutions with additional water may generate significant heat. The addition of water to inorganic acids often generates sufficient heat in the small region of mixing to cause some of the water to boil explosively. | |

PACKAGE MATERIAL INCOMPATIBILITIES

Not Available

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

| Source | Ingredient | Material name | TWA | STEL | Peak | Notes |
|---|----------------------------|---|------------------|------------------|------------------|-----------------------|
| US OSHA Permissible Exposure Levels (PELs) - Table Z1 | sulfuric acid | Sulfuric acid | 1 mg/m3 | Not Available | Not Available | Not Available |
| US ACGIH Threshold Limit Values (TLV) | sulfuric acid | Sulfuric acid | 0.2 mg/m3 | Not Available | Not Available | TLV® Basis: Pulm func |
| US NIOSH Recommended Exposure Limits (RELs) | sulfuric acid | Battery acid, Hydrogen sulfate, Oil of vitriol, Sulfuric acid (aqueous) | 1 mg/m3 | Not Available | Not Available | Not Available |
| US OSHA Permissible Exposure Levels (PELs) - Table Z1 | ammonium heptamolybdate | Molybdenum - Soluble compounds | 5 mg/m3 | Not Available | Not Available | (as Mo) |
| US NIOSH Recommended Exposure Limits (RELs) | ammonium heptamolybdate | Synonyms vary depending upon the specific soluble molybdenum compound. | Not Available | Not Available | Not Available | See Appendix D |

EMERGENCY LIMITS

| Ingredient | Material name | TEEL-1 | TEEL-2 | TEEL-3 |
|-------------------------|---|---------------|---------------|---------------|
| sulfuric acid | Sulfuric acid | Not Available | Not Available | Not Available |
| ammonium heptamolybdate | Molybdic acid, hexaammonium salt; (Ammonium heptamolybdate) | 2.6 mg/m3 | 29 mg/m3 | 170 mg/m3 |

| Ingredient | Original IDLH | Revised IDLH |
|-------------------------|-----------------------|---------------|
| water | Not Available | Not Available |
| sulfuric acid | 80 mg/m3 | 15 mg/m3 |
| ammonium heptamolybdate | N.E. mg/m3 / N.E. ppm | 1,000 mg/m3 |

Exposure controls

Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly.

Personal protection











r craonar protection

▶ Safety glasses with unperforated side shields may be used where continuous eye protection is desirable, as in laboratories; spectacles are not sufficient where complete eye protection is needed such as when handling bulk-quantities, where there is a danger of splashing, or if the material may be under pressure.

Eye and face protection

- ▶ Chemical goggles.whenever there is a danger of the material coming in contact with the eyes; goggles must be properly fitted.
- Full face shield (20 cm, 8 in minimum) may be required for supplementary but never for primary protection of eyes; these afford face protection.
- Alternatively a gas mask may replace splash goggles and face shields.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants.

Print Date: 12/03/2015

Version No: **2.2** Page **5** of **9** Issue Date: **03/09/2014**

Activator Solution for Silica CHEMets, ULR CHEMets, and Vacu-vials Kits

| Skin protection | See Hand protection below |
|-----------------------|---|
| Hands/feet protection | Elbow length PVC gloves When handling corrosive liquids, wear trousers or overalls outside of boots, to avoid spills entering boots. NOTE: The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact. Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed. |
| Body protection | See Other protection below |
| Other protection | Overalls. PVC Apron. PVC protective suit may be required if exposure severe. Eyewash unit. Ensure there is ready access to a safety shower. |
| Thermal hazards | Not Available |

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the *computer-generated* selection:

Activator Solution for Silica CHEMets, ULR CHEMets, and Vacu-vials Kits

| Material | СРІ |
|------------------|-----|
| NEOPRENE | A |
| BUTYL | С |
| NATURAL RUBBER | С |
| NATURAL+NEOPRENE | С |
| NEOPRENE/NATURAL | С |
| NITRILE | С |
| PE | С |
| PVA | С |
| PVC | С |
| SARANEX-23 | С |
| VITON | С |

^{*} CPI - Chemwatch Performance Index

A: Best Selection

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

Respiratory protection

Type E-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Print Date: 12/03/2015

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

| Required Minimum Protection Factor | Half-Face Respirator | Full-Face Respirator | Powered Air Respirator |
|---------------------------------------|-------------------------|-------------------------|----------------------------|
| up to 10 x ES | E-AUS P2 | - | E-PAPR-AUS / Class 1 P2 |
| up to 50 x ES | - | E-AUS / Class 1 P2 | - |
| up to 100 x ES | - | E-2 P2 | E-PAPR-2 P2 ^ |

^{^ -} Full-face

 $A(All\ classes) = Organic\ vapours,\ B\ AUS\ or\ B1 = Acid\ gasses,\ B2 = Acid\ gas\ or\ hydrogen\ cyanide(HCN),\ E = Sulfur\ dioxide(SO2),\ G = Agricultural\ chemicals,\ K = Ammonia(NH3),\ Hg = Mercury,\ NO = Oxides\ of\ nitrogen,\ MB = Methyl\ bromide,\ AX = Low\ boiling\ point\ organic\ compounds(below\ 65\ degC)$

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

| Appearance | colorless | | |
|--|----------------|--|---------------|
| | | | |
| Physical state | Liquid | Relative density (Water = 1) | 1.26 |
| Odour | Odourless | Partition coefficient n-octanol / water | Not Available |
| Odour threshold | Not Available | Auto-ignition temperature (°C) | Not Available |
| pH (as supplied) | <1 | Decomposition temperature | Not Available |
| Melting point / freezing point (°C) | 0 | Viscosity (cSt) | Not Available |
| Initial boiling point and boiling range (°C) | 132 | Molecular weight (g/mol) | Not Available |
| Flash point (°C) | Not Applicable | Taste | Not Available |
| Evaporation rate | Not Available | Explosive properties | Not Available |
| Flammability | Not Applicable | Oxidising properties | Not Available |
| Upper Explosive Limit (%) | Not Available | Surface Tension (dyn/cm or mN/m) | Not Available |
| Lower Explosive Limit (%) | Not Available | Volatile Component (%vol) | Not Available |
| Vapour pressure (kPa) | Not Available | Gas group | Not Available |
| Solubility in water (g/L) | Miscible | pH as a solution | Not Available |

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

^{*} Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

Version No: 2.2 Page 6 of 9

Activator Solution for Silica CHEMets, ULR CHEMets, and Vacu-vials Kits

Issue Date: **03/09/2014**Print Date: **12/03/2015**

| Vapour density (Air = 1) | Not Available | VOC g/L | Not Available |
|--------------------------|---------------|---------|---------------|
| | | | |

SECTION 10 STABILITY AND REACTIVITY

| Reactivity | See section 7 |
|------------------------------------|---|
| Chemical stability | Contact with alkaline material liberates heat Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur. |
| Possibility of hazardous reactions | See section 7 |
| Conditions to avoid | See section 7 |
| Incompatible materials | See section 7 |
| Hazardous decomposition products | See section 5 |

SECTION 11 TOXICOLOGICAL INFORMATION

Skin Irritation/Corrosion

| Inhaled | The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Corrosive acids can cause irritation of the respiratory tract, with coughing, choking and mucous membrane damage. There may be dizziness, headache, nausea and weakness. Not normally a hazard due to non-volatile nature of product The material has NOT been classified by EC Directives or other classification systems as "harmful by inhalation". | | | |
|---|--|--|---|--|
| Ingestion | Ingestion of acidic corrosives may produce burns around and in the mouth, the throat and oesophagus. Immediate pain and difficulties in swallowing and speaking may also be evident. The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. Molybdenum, an essential trace element, can in large doses hamper growth and cause loss of appetite, listlessness and diarrhoea. | | | |
| Skin Contact | Skin contact with acidic corrosives may result in pain and burns; these may be deep with distinct edges and may heal slowly with the formation of scar tissue. Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. | | | |
| Еуе | If applied to the eyes, this material causes severe eye damage. Direct eye contact with acid corrosives may produce pain, tears, sensitivity to light completely. | t and burns. Milo | I burns of the epithelia generally recover rapidly and | |
| Chronic | Repeated or prolonged exposure to acids may result in the erosion of teeth, swell and inflammation of lung tissue often occurs. Substance accumulation, in the human body, is likely and may cause some concent Long-term exposure to respiratory irritants may result in disease of the airways in Skin contact with the material is more likely to cause a sensitisation reaction in sor | n following repea volving difficult b | ated or long-term occupational exposure. reathing and related systemic problems. | |
| Activator Solution for Silica CHEMets, ULR CHEMets, and Vacu-vials Kits | TOXICITY | IRRITATION | | |
| Activator Solution for Silica CHEMets, ULR CHEMets, and Vacu-vials Kits | TOXICITY | IRRITATION | | |
| Activator Solution for Silica CHEMets, ULR CHEMets, and Vacu-vials Kits | The following information refers to contact allergens as a group and may not be Contact allergies quickly manifest themselves as contact eczema, more rarely a involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. If mediated immune reactions. The significance of the contact allergen is not simple and the opportunities for contact with it are equally important. | as urticaria or Qu Other allergic sk | uincke's oedema. The pathogenesis of contact eczema in reactions, e.g. contact urticaria, involve antibody- | |
| WATER | No significant acute toxicological data identified in literature search. | | | |
| SULFURIC ACID | Occupational exposures to strong inorganic acid mists of sulfuric acid: | | | |
| SULFURIC ACID, AMMONIUM HEPTAMOLYBDATE | Asthma-like symptoms may continue for months or even years after exposure to as reactive airways dysfunction syndrome (RADS) which can occur following explications of RADS include the absence of preceding respiratory disease, in a nawithin minutes to hours of a documented exposure to the irritant. A reversible air bronchial hyperreactivity on methacholine challenge testing and the lack of mining in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating in of and duration of exposure to the irritating substance. | xposure to high non-atopic individual rflow pattern, on mal lymphocytic | levels of highly irritating compound. Key criteria for the dual, with abrupt onset of persistent asthma-like symptoms spirometry, with the presence of moderate to severe inflammation, without eosinophilia, have also been included | |
| Acute Toxicity | ○ Car | rcinogenicity | 0 | |
| · | | - | | |

Reproductivity

0

Version No: 2.2 Page 7 of 9 Issue Date: 03/09/2014 Print Date: 12/03/2015

Activator Solution for Silica CHEMets, ULR CHEMets, and Vacu-vials Kits

Serious Eye STOT - Single Exposure Damage/Irritation Respiratory or Skin STOT - Repeated Exposure sensitisation 0 0 Mutagenicity Aspiration Hazard

Legend:

— Data required to make classification available 🗶 – Data available but does not fill the criteria for classification

Data Not Available to make classification

CMR STATUS

| CARCINOGEN | sulfuric acid US Environmental Defense Scorecard Recognized Carcinogens P65 | |
|-------------|--|---|
| RESPIRATORY | sulfuric US - California OEHHA/ARB - Acute Reference Exposure Levels and Target Organs (RELs) - Respiratory US - California acid OEHHA/ARB - Chronic Reference Exposure Levels and Target Organs (CRELs) - Respiratory | X |

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

Ecotoxicity:

The tolerance of water organisms towards pH margin and variation is diverse. Recommended pH values for test species listed in OECD guidelines are between 6.0 and almost 9. Acute testing with fish showed 96h-LC50 at about pH 3.5

For Molybdenum:

Environmental Fate: Molybdenum is an essential micronutrient in plants and animals. It is commonly used in the manufacture of steel alloys. Based on the high concentration of molybdenum in all analyzed waste types, the exposure of the environment to molybdenum is regarded as significant.

Persistence and degradability

| Ingredient | Persistence: Water/Soil | Persistence: Air |
|------------|-------------------------|------------------|
| water | LOW | LOW |

Bioaccumulative potential

| Ingredient | Bioaccumulation |
|-------------------------|----------------------|
| water | LOW (LogKOW = -1.38) |
| ammonium heptamolybdate | LOW (BCF = 5.7) |

Mobility in soil

| Ingredient | Mobility |
|------------|------------------|
| water | LOW (KOC = 14.3) |

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal

Dispose of according to federal, state, and local regulations.

SECTION 14 TRANSPORT INFORMATION

Labels Required



Marine Pollutant

Land transport (DOT)

| Lana transport (DOT) | |
|------------------------------|--|
| UN number | 1760 |
| Packing group | |
| UN proper shipping name | Corrosive liquids, n.o.s. (contains sulfuric acid) |
| Environmental hazard | No relevant data |
| Transport hazard class(es) | Class 8 |
| Special precautions for user | Special provisions B2, IB2, T11, TP2, TP27 |

Air transport (ICAO-IATA / DGR)

| UN number | 1760 |
|---------------|------|
| Packing group | II |

Version No: **2.2** Page **8** of **9** Issue Date: **03/09/2014**

Activator Solution for Silica CHEMets, ULR CHEMets, and Vacu-vials Kits

Print Date: 12/03/2015

| UN proper shipping name | Corrosive liquid, n.o.s. * (contains sulfuric acid) | |
|------------------------------|--|--------|
| Environmental hazard | No relevant data | |
| Transport hazard class(es) | ICAO/IATA Class 8 ICAO / IATA Subrisk Not Applicable ERG Code 8L | |
| Special precautions for user | Special provisions | A3A803 |
| | Cargo Only Packing Instructions | 855 |
| | Cargo Only Maximum Qty / Pack | 30 L |
| | Passenger and Cargo Packing Instructions | 851 |
| | Passenger and Cargo Maximum Qty / Pack | 1 L |
| | Passenger and Cargo Limited Quantity Packing Instructions | Y840 |
| | Passenger and Cargo Limited Maximum Qty / Pack | 0.5 L |

Sea transport (IMDG-Code / GGVSee)

| UN number | 1760 |
|------------------------------|--|
| Packing group | II . |
| UN proper shipping name | CORROSIVE LIQUID, N.O.S. (contains sulfuric acid) |
| Environmental hazard | Not Applicable |
| Transport hazard class(es) | IMDG Class 8 IMDG Subrisk Not Applicable |
| Special precautions for user | EMS Number F-A , S-B Special provisions 274 Limited Quantities 1 L |

Transport in bulk according to Annex II of MARPOL 73 / 78 and the IBC code

| Source | Ingredient | Pollution Category |
|---|---------------|--------------------|
| IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk | sulfuric acid | Y |

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

| water(7732-18-5) is found on the following regulatory lists | "US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory" |
|---|--|
| sulfuric acid(7664-93-9) is found on the following regulatory lists | "US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants", "US - Idaho - Limits for Air Contaminants", "US - Hawaii Air Contaminant Limits", "US - California Permissible Exposure Limits for Chemical Contaminants", "US ACGIH Threshold Limit Values (TLV) - Carcinogens", "US National Toxicology Program (NTP) 13th Report Part A Known to be Human Carcinogens", "US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants", "US - Oregon Permissible Exposure Limits (Z-1)", "US - Michigan Exposure Limits for Air Contaminants", "International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs", "US - Washington Toxic air pollutants and their ASIL, SQER and de minimis emission values", "US - California OEHHA/ARB - Acute Reference Exposure Levels and Target Organs (RELs)", "US NIOSH Recommended Exposure Limits (RELs)", "International Air Transport Association (IATA) Dangerous Goods Regulations - Prohibited List Passenger and Cargo Aircraft", "US - Alaska Limits for Air Contaminants", "US - Washington Permissible exposure limits of air contaminants", "US - Minnesota Permissible Exposure Limits (PELs)", "US - California OEHHA/ARB - Chronic Reference Exposure Levels and Target Organs (CRELs)", "US ACGIH Threshold Limit Values (TLV)", "US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants", "US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory", "US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants", "US - New Jersey Right to Know - Special Health Hazard Substance List (SHHSL): Carcinogens", "US OSHA Permissible Exposure Levels (PELs) - Table Z1" |
| ammonium heptamolybdate(12027-67-7) is found on the following regulatory lists | "US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants","US - Idaho - Limits for Air Contaminants","US - Hawaii Air Contaminant Limits","US - California Permissible Exposure Limits for Chemical Contaminants","US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants","US - Oregon Permissible Exposure Limits (Z-1)","US - Michigan Exposure Limits for Air Contaminants","US NIOSH Recommended Exposure Limits (RELs)","US - Alaska Limits for Air Contaminants","US - Washington Permissible exposure limits of air contaminants","US - Minnesota Permissible Exposure Limits (PELs)","US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants","US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory","US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants","US OSHA Permissible Exposure Levels (PELs) - Table Z1" |

SECTION 16 OTHER INFORMATION

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net/references

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any

Version No: 2.2 Page 9 of 9 Issue Date: 03/09/2014 Print Date: 12/03/2015

Activator Solution for Silica CHEMets, ULR CHEMets, and Vacu-vials Kits

process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.