Page 1/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 30.11.2017 Version number 83 Revision: 30.11.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Product name: COD / CSB 0-150 mg/l

· Catalog number: 424433, 2420720, 420720, 2420725, 420725

- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Application of the substance / the preparation: Reagent for water analysis
- · 1.3 Details of the supplier of the safety data sheet

· Supplier:

Tintometer GmbH Schleefstraße 8-12 44287 Dortmund Made in Germany www.lovibond.com

Tintometer GmbH Division AQUALYTIC® Schleefstr. 12 44287 Dortmund Made in Germany www.aqualytic.de

The Tintometer Limited Lovibond® House Sun Rise Way Amesbury Wiltshire SP4 7GR United Kingdom

· Informing department:

e-mail: produktsicherheit@tintometer.de

Product Safety Department

1.4 Emergency telephone number:

Poison Center Berlin, Germany phone: 0049 30 30686 790 Languages: English and German

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS06 skull and crossbones

Acute Tox. 3 H311 Toxic in contact with skin.



GHS08 health hazard

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS05 corrosion

Met. Corr.1 H290 May be corrosive to metals.

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

(Contd. on page 2)

phone: +49 231 94510-0

e-mail: sales@tintometer.de

phone: +49 231 94510-755

e-mail: sales@aqualytic.de

phone: +44 1980 664800

e-mail: SDS@tintometer.com

Printing date 30.11.2017 Version number 83 Revision: 30.11.2017

Product name: COD / CSB 0-150 mg/l

(Contd. of page 1)



GHS09 environment

Aquatic Acute 1 H400 Very toxic to aquatic life.

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.



Acute Tox. 4 H302 Harmful if swallowed.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.
- · Hazard pictograms









GHS05

5 GHS06

GHS08 GHS

- · Signal word Danger
- · Hazard-determining components of labelling:

sulphuric acid 82 % mercury sulphate

· Hazard statements

H290 May be corrosive to metals.

H302 Harmful if swallowed.

H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H373 May cause damage to organs through prolonged or repeated exposure.

H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

P260 Do not breathe mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing.

P308+P310 IF exposed or concerned: Immediately call a POISON CENTER/doctor.

2.3 Other hazards

Contact with skin and inhalation of aerosols/ vapours of the preparation should be avoided.

Acid burns have to treated immediately, as it may otherwise cause badly curing wounds.

CAS 7783-35-9: Danger by skin resorption.

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be persistent, bioaccumulative and toxic (PBT) or very persistent and very bioaccumulative (vPvB), according to the criteria given in Annex XIII of Regulation (EC) No. 1907/2006.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: sulfuric acid solution

Dangerous components:

The percent content of the chromium compound mentioned below refers to the amount of chromate ions dissolved in water. The percent content of the mercury compound mentioned below refers to the amount of the pure mercury therein.

(Contd. on page 3)

Printing date 30.11.2017 Version number 83 Revision: 30.11.2017

Product name: COD / CSB 0-150 mg/l

	(Cor	ntd. of page 2)
CAS: 7783-35-9 EINECS: 231-992-5 Index No: 080-002-00-6	mercury sulphate Acute Tox. 2, H300; Acute Tox. 1, H310; Acute Tox. 2, H330; STOT RE 2, H373; Acute Acute 1, H400; Aquatic Chronic 1, H410	0.25–1%
CAS: 10294-26-5 EINECS: 233-653-7	disilver(1+) sulphate ♦ Eye Dam. 1, H318; ♦ Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100)	0.25–1%
CAS: 7778-50-9 EINECS: 231-906-6 Index No: 024-002-00-6 Reg.nr.: 01-2119454792-32-XXXX Skin Corr. 1B, H314; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H312; Skin Sens. 1, H317		<0.1% 1,

[·] Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

General information

Personal protection for the First Aider!

Instantly remove any clothing soiled by the product.

· After inhalation

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness bring patient into stable side position for transport.

· After skin contact

Wash with polyethylene glycol 400 and then rinse with copious amounts of water.

Immediate medical treatment necessary. Failure to treat burns can prevent wounds from healing.

After eye contact

Rinse opened eye for several minutes (at least 15 min) under running water.

Call a doctor immediately.

· After swallowing

Rinse out mouth and then drink 1-2 glasses of water.

Do not induce vomiting; instantly call for medical help.

4.2 Most important symptoms and effects, both acute and delayed:

burns

absorption

after inhalation:

breathing difficulty

coughing

asthma attacks

damage to the affected mucous membranes

after swallowing:

metallic taste

sickness

vomiting

bloody diarrhoea

pain

strong caustic effect.

unconsciousness

methaemoglobin formation

cramps

Danger

Danger of system failure.

Danger of gastric perforation.

Danger of pulmonary oedema.

4.3 Indication of any immediate medical attention and special treatment needed:

If swallowed or in case of vomiting, danger of entering the lungs Subsequent observation for pneumonia and pulmonary oedema

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents CO₂, sand, extinguishing powder.
- For safety reasons unsuitable extinguishing agents Water.

Printing date 30.11.2017 Version number 83 Revision: 30.11.2017

Product name: COD / CSB 0-150 mg/l

(Contd. of page 3)

· 5.2 Special hazards arising from the substance or mixture

The product is not combustible.

Formation of toxic gases is possible during heating or in case of fire.

Sulphur oxides (SOx)

mercury vapours

5.3 Advice for firefighters

Protective equipment:

Wear self-contained breathing apparatus.

Wear full protective suit.

· Additional information

Collect contaminated fire fighting water separately. It must not enter drains.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Ambient fire may liberate hazardous vapours.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel:

Wear protective equipment. Keep unprotected persons away.

Avoid substance contact.

Ensure adequate ventilation

Use breathing protection against the effects of fumes/dust/aerosol.

· Advice for emergency responders: Protective equipment: see section 8

6.2 Environmental precautions:

Do not allow product to reach sewage system or water bodies.

Prevent material from reaching sewage system, holes and cellars.

Inform respective authorities in case product reaches water or sewage system.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Use neutralising agent.

Neutralize with diluted sodium hydroxide solution.

Absorb with liquid-binding material (sand, diatomite, universal binders).

Dispose of contaminated material as waste according to item 13.

6.4 Reference to other sections

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

· Advice on safe handling:

Open and handle container with care.

Work only in fume cupboard.

Prevent formation of aerosols.

· Hygiene measures:

Do not inhale gases / fumes / aerosols.

Do not get in eyes, on skin, or on clothing.

Take off immediately all contaminated clothing.

Wash hands during breaks and at the end of the work.

Do not eat, drink or smoke when using this product.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage

Requirements to be met by storerooms and containers: Store in cool location.

Information about storage in one common storage facility:

Store away from metals.

Do not store together with alkalis (caustic solutions).

Store away from flammable substances.

Further information about storage conditions:

Store in a locked cabinet or with access restricted to technical experts or their assistants.

Store in cool, dry conditions in well sealed containers.

Protect from heat and direct sunlight.

Protect from the effects of light.

Protect from humidity and keep away from water.

Printing date 30.11.2017 Version number 83 Revision: 30.11.2017

Product name: COD / CSB 0-150 mg/l

(Contd. of page 4)

This product is hygroscopic. Store under dry conditions.

- Recommended storage temperature: 20°C +/- 5°C
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

51. 55.m5. parameter			
· Components with limit values that require monitoring at the workplace:			
CAS: 7664-93-9 sulphur	CAS: 7664-93-9 sulphuric acid		
WEL (Great Britain)	Long-term value: 0.05* mg/m³ *mist: defined as thoracic fraction		
IOELV (European Union)	Long-term value: 0.05 mg/m³		
OEL (Sweden)	Short-term value: 0.2 mg/m³ Long-term value: 0.1 mg/m³ C, V		
CAS: 7783-35-9 mercury	sulphate		
WEL (Great Britain)	Long-term value: 0.02 mg/m³ as Hg		
IOELV (European Union)	Long-term value: 0.02 mg/m³ as Hg		
OEL (Sweden)	Long-term value: 0.02 mg/m³ inhalerbart damm, som Hg; B		
CAS: 10294-26-5 disilver(1+) sulphate			
WEL (Great Britain)	Long-term value: 0.01 mg/m³ as Ag		
OEL (Sweden)	Long-term value: 0.1 mg/m³ som Ag, totaldamm		

· Regulatory information

WEL (Great Britain): EH40/2011

IOELV (European Union): (EU) 2017/164

OEL (Sweden): AFS2015:7

· Additional information: IOELV = Indicative Occupational Exposure Limit

DNELs

Derived No Effect Level (DNEL)

CAS: 7664-93-9 sulphuric acid		
Inhalative [DNEL	0.1 mg/m³ (Worker / acute / local effects)
		0.05 mg/m³ (Worker / acute / systemic effects)

Recommended monitoring procedures:

Methods for measurement of the workplace atmosphere have to correspond to the requirements of norms DIN EN 482 and DIN EN 689.

· PNECs

Predicted No Effect Concentration (PNEC)

	CAS: 7664-93-9 sulphuric acid			
PNEC	8.8 mg/l (Sewage treatment plant)			
	0.00025 mg/l (Marine water)			
	0.0025 mg/l (Fresh water)			
PNEC	0.002 mg/kg (Marine sediment)			
	0.002 mg/kg (Fresh water sediment)			

· Ingredients with biological limit values:

CAS: 7783-35-9 mercury sulphate

BMGV (Great Britain) 20 µmol/mol creatinine

Medium: urine
Sampling time: random
Parameter: mercury

· Regulatory information BMGV (Great Britain): EH40/2011

Printing date 30.11.2017 Version number 83 Revision: 30.11.2017

Product name: COD / CSB 0-150 mg/l

(Contd. of page 5)

- · Additional information: The lists that were valid during the compilation were used as basis.
- · 8.2 Exposure controls
- · Engineering measures:

Technical measures and appropriate working operations should be given priority over the use of personal protective equipment. See item 7.

- · Personal protective equipment
- · Breathing equipment: Use breathing protection against the effects of fumes/dust/aerosol.
- · Recommended filter device for short term use: Combination filter B-P2
- · Protection of hands:

Acid resistant gloves

Preventive skin protection by use of skin-protecting agents is recommended.

After use of gloves apply skin-cleaning agents and skin cosmetics.

· Material of gloves

Butyl rubber, BR

Recommended thickness of the material: > 0.3 mm

· Penetration time of glove material

Value for the permeation: Level = 1 (< 10 min)

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

Tightly sealed safety glasses.

Face protection

- · Body protection: Acid resistant protective clothing
- · Limitation and supervision of exposure into the environment:

Do not allow product to reach sewage system or water bodies.

Avoid release to the environment.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties · Appearance:		
Form / Physical state:	Liquid	
Colour:	Yellow-brown	
· Odour: Recognisable		
· Odour threshold:	Not determined.	
· pH-value at 20 °C:	1	
· Melting point/Freezing point: · Initial boiling point and boiling range	Not determined e: > 100 °C	
· Flash point:	Not applicable	
· Flammability (solid, gas):	Not applicable.	
Decomposition temperature:	Not determined.	
· Auto-ignition temperature:	Product is not self-igniting.	
· Explosive properties: · Flammability or explosive limits:	Product is not explosive.	
Lower:	Not applicable	
Upper:	Not applicable	
· Oxidising properties:	CAS 7664-93-9 : Oxidising potential	
· Vapour pressure:	Not determined.	
Density at 20 °C:	1,76 g/cm³	
Relative density:	Not determined.	
Vapour density:	Not determined.	
· Evaporation rate:	Not determined.	
· Solubility(ies):		
Water:	Fully miscible	

(Contd. on page 7)

Printing date 30.11.2017 Version number 83 Revision: 30.11.2017

Product name: COD / CSB 0-150 mg/l

(Contd. of page 6)

	(*************************************	
· Partition coefficient: n-octanol/water: Not determined.		
· Viscosity:	Not determined.	
· Solvent content:		
Organic solvents:	0,0 %	
Water:	< 20 %	
Solids content:	< 5 %	
· 9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity see section 10.3
- · 10.2 Chemical stability Stable at ambient temperature (room temperature).
- 10.3 Possibility of hazardous reactions

Corrosive action on metals

Reacts with metals forming hydrogen (--> Explosive!)

When diluting, always add acid to water, never vice versa

Diluting or dissolving in water always causes rapid heating

Reacts with reducing agents

Reacts with acids, alkalis and oxidizing agents

Reacts with peroxides

Reacts with halogenated compounds

Reacts with ammonia (NH₃).

- 10.4 Conditions to avoid strong heating
- · 10.5 Incompatible materials:

metals

combustible substances

organic solvents

organic substances

· 10.6 Hazardous decomposition products: see section 5

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity

Classification according to calculation procedure:

Harmful if swallowed.

Toxic in contact with skin.

TONG IT CONTROL WITH SKITT.					
· Acute tox	· Acute toxicity estimate (ATE _(MIX)) - Calculation method:				
Oral	CLP ATE(MIX)	694 mg/kg (.)			
Dermal	CLP ATE(MIX)	694 mg/kg (.)			
Inhalative	CLP ATE(MIX)	6.9 mg/l/4h (aerosol)			
· LD/LC50 v	values that a	are relevant for classification:			
CAS: 766	4-93-9 sulph	uric acid			
Oral		2140 mg/kg (rat) IUCLID)			
		o10 mg/m³/2h (rat) UCLID			
CAS: 778	3-35-9 mercı	ury sulphate			
Oral	LD50 5	5 mg/kg (ATE)			
		77 mg/kg (rat) RTECS)			
Dermal	LD50 5	5 mg/kg (ATE)			
	LD50. 6	S25 mg/kg (rat)			
Inhalative	LC50 0	0.05 mg/l/4h (ATE)			
		(Contd. on norse 0)			

Printing date 30.11.2017 Version number 83 Revision: 30.11.2017

Product name: COD / CSB 0-150 mg/l

(Contd. of page 7) CAS: 10294-26-5 disilver(1+) sulphate LD50 >5000 mg/kg (rat) (OECD 401) Oral (Registrant, ECHA) CAS: 7778-50-9 potassium dichromate Oral LD50 90.5 mg/kg (rat) (OECD 401) (ECHA, registrant: LD50 = 90.5 mg/kg female to 168.0 mg/kg male) **LDLo** 26 mg/kg (child) 143 mg/kg (man) 1170 mg/kg (rat) Dermal LD50 (IUCLID) Inhalative LC50 0.094 mg/l/4h (rat) (OECD 403, Aerosol) LD50 IPR 28 mg/kg (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes severe skin burns and eye damage.

Serious eye damage/irritation

Causes serious eye damage.

Risk of blindness!

· Information on	· Information on components:				
CAS: 10294-26-	CAS: 10294-26-5 disilver(1+) sulphate				
Irritation of skin	OECD 404	(rabbit: no irritation)			
Irritation of eyes		· · · · · · · · · · · · · · · · · · ·			
CAS: 7778-50-9	CAS: 7778-50-9 potassium dichromate				
Irritation of skin	OECD 404	(rabbit: irritation)			

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Information on components:

CAS 7778-50-9: Sensitizing effect by inhalation and skin contact is possible by prolonged exposure.

CAS: 7778-5	CAS: 7778-50-9 potassium dichromate		
Sensitisation	Patch test (human)		
		(IUCLID)	

- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction) The following statements refer to the mixture:
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT (specific target organ toxicity) -single exposure Based on available data, the classification criteria are not met.
- STOT (specific target organ toxicity) -repeated exposure

May cause damage to organs through prolonged or repeated exposure.

- · Aspiration hazard Based on available data, the classification criteria are not met.
- · Additional toxicological information:

Mercury compounds have a cytotoxic and protoplasmatoxic effect.

The principal signs manifest themselves in the CNS.

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

The aerosol is corrosive to the eyes, the skin and the respiratory tract. Inhalation of aerosols may cause lung oedema.

Sulfuric acid: erosion of the teeth, cancer

SECTION 12: Ecological information

· 12.1 Toxicity

12.1 TOXIOLY				
· Aquati	· Aquatic toxicity:			
CAS: 7	CAS: 7664-93-9 sulphuric acid			
EC50	>100 mg/l/48h (Daphnia magna) (OECD 202) (ECHA)			
LC50	16–29 mg/l/96h (bluegill) (Merck)			
	(Contd. on page 0)			

Printing date 30.11.2017 Version number 83 Revision: 30.11.2017

Product name: COD / CSB 0-150 mg/l

	(Contd. of page 8)
CAS: 7	783-35-9 mercury sulphate
LC50	0.5 mg/l/48h (gold orfe)
EC50	0.005–3.6 mg/l/48h (Daphnia magna)
LC50	0.19 mg/l/96h (fathhead minnow)
CAS: 1	0294-26-5 disilver(1+) sulphate
EC50	0.0045 mg/l/48h (Daphnia magna) (GESTIS)
EC50	0.0049 mg/l/96h (fathhead minnow)
EC10	0.00214 mg/l (Daphnia magna) (ASTM) (21d, test substance: AgNO ₃)
	0.00039 mg/l (fathhead minnow) (ASTM E1241-98) (28d, test substance: AgNO ₃ , result in mg/l Ag)
CAS: 7	778-50-9 potassium dichromate
EC50	0.62 mg/l/48h (Daphnia magna) (OECD 202) (Merck)
NOEC	0.016–0.064 mg/l (Daphnia magna) (7d)
	6 mg/l (fathhead minnow) (7d)
IC50	0.16–0.59 mg/l/96 h (Chlorella vulgaris) (IUCLID)
EC50	0.31 mg/l/72 h (Desmodesmus subspicatus)
LC50	58.5 mg/l/96h (byr)
	0.131 mg/l/96h (bluegill)
	160 mg/l/96h (guppy)
	26.13 mg/l/96h (fathhead minnow) (Merck/IUCLID)

Bacterial toxicity:

sulphates toxic > 2.5 g/l

CAS: 7778-50-9 potassium dichromate

EC50 58 mg/l (Photobacterium phosphoreum) (30 min; Microtox-Test)

Other information:

Toxic for fish:

sulphates > 7 g/l

12.2 Persistence and degradability

Other information:

Mixture of inorganic compounds.

Methods for the determination of biodegradability are not applicable to inorganic substances.

12.3 Bioaccumulative potential

BCF = Bioconcentration factor

CAS: 10294-26-5 disilver(1+) sulphate BCF | 2.5 (rainbow trout) | (8d, 15°C, test substance: AgNO₃) CAS: 7778-50-9 potassium dichromate BCF | 17.4 (rainbow trout)

12.4 Mobility in soil No further relevant information available.

· 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be persistent, bioaccumulative and toxic (PBT) or very persistent and very bioaccumulative (vPvB), according to the criteria given in Annex XIII of Regulation (EC) No. 1907/2006.

12.6 Other adverse effects

Harmful effect due to pH shift.

Forms corrosive mixtures with water even if diluted.

Avoid transfer into the environment.

Water hazard:

Do not allow product to reach ground water, water bodies or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into soil.

Printing date 30.11.2017 Version number 83 Revision: 30.11.2017

Product name: COD / CSB 0-150 mg/l

(Contd. of page 9)

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Hand over to disposers of hazardous waste.

European waste catalogue

16 05 07 discarded inorganic chemicals consisting of or containing dangerous substances

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleaning agent: Water, if necessary with cleaning agent.

SECTION 14: Transport information	
· 14.1 UN-Number · ADR, IMDG, IATA	UN2922
· 14.2 UN proper shipping name · ADR	2922 CORROSIVE LIQUID, TOXIC, N.O.S. (SULPHURIC ACID MERCURY SULPHATE), ENVIRONMENTALLY HAZARDOUS
· IMDG	CORROSIVE LIQUID, TOXIC, N.O.S. (SULPHURIC ACID, MERCURY SULPHATE), MARINE POLLUTANT
· IATA	CORROSIVE LIQUID, TOXIC, N.O.S. (SULPHURIC ACID, MERCURY SULPHATE)
· 14.3 Transport hazard class(es)	
ADR	
· Class · Label	8 (CT1) Corrosive substances. 8+6.1
· IMDG	
· Class · Label	8 Corrosive substances. 8/6.1
·IATA	
· Class · Label	8 Corrosive substances. 8 (6.1)
· 14.4 Packing group · ADR, IMDG, IATA	II
· 14.5 Environmental hazards: · Marine pollutant:	Yes
· Special marking (ADR):	Symbol (fish and tree) Symbol (fish and tree)
· 14.6 Special precautions for user · Kemler Number: · EMS Number:	Warning: Corrosive substances. 86 F-A,S-B
Segregation groups	Acids

Printing date 30.11.2017 Version number 83 Revision: 30.11.2017

Product name: COD / CSB 0-150 mg/l

(Contd. of page 10)

	(Conta. or page 10)
· Stowage Category · Stowage Code	B SW2 Clear of living quarters.
· 14.7 Transport in bulk according to Annex II of Marpol the IBC Code	l and Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category · Tunnel restriction code	2 E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E2

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Regulation (EC) No 689/2008 concerning the export and import of dangerous chemicals:

None of the ingredients is listed.

· Regulation (EC) No 1005/2009 on substances that deplete the ozone layer:

None of the ingredients is listed.

- · Directive 2012/18/EU (SEVESO III):
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category E1 Hazardous to the Aquatic Environment
- Qualifying quantity (tonnes) for the application of lower-tier requirements 100 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 18
- · Information about limitation of use:

Observe employment restrictions for pregnant and nursing mothers according to the 'mother protection guideline' (92/85/EEC) . Employment restrictions concerning young persons must be observed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H272 May intensify fire; oxidiser.
- H290 May be corrosive to metals.
- H300 Fatal if swallowed.
- H301 Toxic if swallowed.
- H310 Fatal in contact with skin.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H330 Fatal if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H340 May cause genetic defects.
- H350 May cause cancer.
- H360FD May damage fertility. May damage the unborn child.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H373 May cause damage to organs through prolonged or repeated exposure.

(Contd. of page 11)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 30.11.2017 Version number 83 Revision: 30.11.2017

Product name: COD / CSB 0-150 mg/l

H400 Very toxic to aquatic life.

Very toxic to aquatic life with long lasting effects. H410

· Training hints Provide adequate information, instruction and training for operators.

· Abbreviations and acronyms:

EC50: effective concentration, 50 percent (in vivo)

OECD: Organisation for Economic Co-operation and Development

STOT: specific target organ toxicity

SE: single exposure

RE: repeated exposure

EC50: half maximal effective concentration

IC50: hallf maximal inhibitory concentration NOEL or NOEC: No Observed Effect Level or Concentration

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RÍD: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of

Dangerous Goods by Rail)
IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Ox. Sol. 2: Oxidizing solids - Category 2

Met. Corr.1: Corrosive to metals - Category 1

Acute Tox. 2: Acute toxicity – Category 2 Acute Tox. 3: Acute toxicity – Category 3

Acute Tox. 1: Acute toxicity – Category 1
Acute Tox. 4: Acute toxicity – Category 1
Acute Tox. 4: Acute toxicity – Category 4
Skin Corr. 1A: Skin corrosion/irritation – Category 1A
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Muta. 1B: Germ cell mutagenicity - Category 1B

Carc. 1B: Carcinogenicity – Category 1B Repr. 1B: Reproductive toxicity – Category 1B

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Data arise from safety data sheets, reference works and literature.

ECHA: European CHemicals Agency http://echa.europa.eu

IUCLID (International Uniform Chemical Information Database)

GESTIS- Stoffdatenbank (Substance Database, Germany)

RTECS (Registry of Toxic Effects of Chemical Substances)

International Chemical Safety Cards (ICSCs)

* Data compared to the previous version altered.

GB