

Ordering information

Product structure TurbiMax W CUS 65

| Measuring range, application | | | | |
|------------------------------|---|---|--|---------------------|
| | A | 0 to 12 g/l, activated sludge, centrate | | |
| | B | 0 to 40 g/l, return sludge | | |
| | C | 0 to 50 g/l, primary sludge, digested sludge | | |
| | D | 1 to 1000 FNU, wastewater effluent, service water, condensate, boiler feedwater | | |
| | E | 10 to 150 g/l, centrifuge inlet, press inlet | | |
| Certificates | | | | |
| | 1 | Factory calibration certificate | | |
| Process connection | | | | |
| | A | G1 + NPT 3/4 thread | | |
| | Y | Special version acc. to customer specification | | |
| Connecting cable | | | | |
| | 1 | 7 m (23 ft), SXP plug | | |
| | 2 | 15 m (49 ft), SXP plug | | |
| | 3 | 1 m (3.3 ft) + extension cable 10 m (32 ft), both with SXP plug | | |
| Seal | | | | |
| | A | Viton | | |
| | Y | Special version acc. to customer specification | | |
| CUS65- | | | | complete order code |

Scope of delivery

The scope of delivery comprises:

- 1 CUS65 sensor, cable length depending on version
- 1 extension cable (only version CUS65-xxx3)
- 1 Quality certificate
- 1 Operating Instructions BA370C/07/en