

| | | |
|-----------------|----------------------------|-------------------------|
| Material | Sensor shaft: | POM |
| | Membrane cap: | POM |
| | Cathode: | Gold |
| | Anode/Reference electrode: | Silver / silver bromide |

Process connection G1 and NPT 3/4"

Maximum cable length max. 50 m (164 ft)

Membrane thickness approx. 50 µm

Electrolyte Alkaline electrolyte

Ordering information

Product structure

| | | Cable length |
|---------|---|---|
| | 2 | Cable length: 7 m (22.97 ft) |
| | 4 | Cable length: 15 m (49.22 ft) |
| | 8 | Without Cable (TOP 68 version only) |
| | 9 | Special design to customer specifications |
| | | Cable connection |
| | F | Fixed cable connection |
| | S | Cable connection using TOP 68 plug |
| COS 41- | | Complete order code |

Scope of delivery

The following items are included in the delivery:

- Oxygen sensor with transport protection cap for membrane protection
- Accessories set with the following contents:
 - 2 replacement cartridges (replacement membrane caps)
 - 10 plastic ampoules containing electrolyte
 - 1 sealing kit with 3 O-rings
 - 6 abrasive sheets
- Operating Instructions (on CD only)
- Brief Operating Instructions (paper version)