

Ordering information

Product structure

Certificate	
A	Ex free version
Cable length	
0	Cable length: 1.5 m (4.9 ft)
1	Cable length: 7 m (23 ft)
2	Cable length: 15 m (49 ft)
8	Without cable (for TOP 68 version)
9	Special version acc. to customers specification
Sensor head	
F	G1, fixed cable with SXP plug
S	G1, TOP68 plug
Accessories	
0	without accessories
COS61-	complete order code

Scope of delivery

The following items are included in the delivery:

- Oxygen sensor with transport protection cap for membrane protection
- Operating Instructions (on CD only)
- Brief Operating Instructions (paper version)

Certificates and approvals

Electromagnetic compatibility

Interference emission and interference immunity complies with EN 61326: 1997 / A1: 1998

Accessories



Note!

In the following sections, you find the accessories available at the time of issue of this documentation. For information on accessories that are not listed here, please contact your responsible service.

Assemblies (selection)

Retractable assembly Cleanfit COA451

- manually driven retractable assembly, stainless steel, with ball valve, for oxygen sensors;
- ordering acc. to product structure (Technical Information TI368C/07/en)

Immersion assembly Dipfit W CYA611

- For sensor immersion in basins, open channels and tanks, PVC
- Ordering acc. to product structure, see Technical Information TI166C/07/en

Flow assembly COA250

- for sensor installation in pipe lines, PVC
- ordering acc. to product structure (Technical Information TI111C/07/en)

Zero solution

- 3 units to produce 3 x 1 liter oxygen-free solution
- order no. 50001041

Measuring cable

COK31 special measuring cable

- for sensors COS31, COS61 and COS71 with TOP68 plug-in head
- Order numbers:
 - Cable length 1.5 m (4.9 ft): 51506820
 - Cable length 7 m (23 ft): 51506821
 - Cable length 15 m (49 ft): 51506822