



4-SIDED FILM APPLICATOR (QUADRUPLEX) VF2167, VF2168, VF2169, VF2170, VF2172, VF2173, VF2174, VF2175

DATASHEET

PRODUCT DESCRIPTION

The TQC 4-Sided Film Applicator (Quadruplex) has four application sides for applying paint films with four different predefined thicknesses, in film width 60 or 80 mm. One side of the applicator is supplied with a guidance support for straight application. This support may be removed as well. The high grade stainless steel will not be affected by acid or base elements.



BUSINESS

Coating Laboratories, Paint production

STANDARDS

ASTM D 823

SCOPE OF SUPPLY

- TQC 4-Sided Film Applicator (Quadruplex)
- Calibration Certificate
- Protective case

ORDERING INFORMATION

VF2167 - 4-Sided film applicator (Quadruplex) width 60mm, with 4 gaps as desired

VF2168 - 4-Sided film applicator (Quadruplex) width 60mm, with 4 gaps: 15/30/60/90 μm

VF2169 - 4-Sided film applicator (Quadruplex) width 60mm, with 4 gaps: 30/60/90/120 μm

VF2170 - 4-Sided film applicator (Quadruplex) width 60mm, with 4 gaps: 50/100/150/200 μm

VF2172 - 4-Sided film applicator (Quadruplex) width 80mm, with 4 gaps as desired

VF2173 - 4-Sided film applicator (Quadruplex) width 80mm, with 4 gaps: 15/30/60/90 μm

VF2174 - 4-Sided film applicator (Quadruplex) width 80mm, with 4 gaps: 30/60/90/120 μm

VF2175 - 4-Sided film applicator (Quadruplex) width 80mm, with 4 gaps: 50/100/150/200 μm

ACCESSORIES

AB3120 - TQC motorized automatic film applicator with glass bed and combined attachment assembly for standard block applicators and spiral bar coaters, 230V

AB3125 - TQC motorized automatic film applicator with glass bed and combined attachment assembly for standard block applicators and spiral bar coaters, 100V

AB3220 - TQC motorized automatic film applicator with perforated vacuum bed, built-in vacuum pump and combined attachment assembly for standard block applicators and spiral bar coaters, 230V

AB3225 - TQC motorized automatic film applicator with perforated vacuum bed, built-in vacuum pump and combined attachment assembly for standard block applicators and spiral bar coaters, 100V





AB3320 - TQC motorized automatic film applicator with double channeled vacuum bed, built-in vacuum pump and combined attachment assembly for standard block applicators and spiral bar coaters, 230V

AB3325 - TQC motorized automatic film applicator with double channeled vacuum bed, built-in vacuum pump and combined attachment assembly for standard block applicators and spiral bar coaters, 100V

AB3400 - TQC motorized automatic film applicator with heated vacuum bed, built-in vacuum pump and combined attachment assembly for standard block applicators and spiral bar coaters 230V

AB3405 - TQC motorized automatic film applicator with heated vacuum bed, built-in vacuum pump and combined attachment assembly for standard block applicators and spiral bar coaters 100V

VF1601 - TQC Application Table 380 x 230

VF1602 - TQC Application Table 230 x 160

VF2343 - TQC Test charts A6, White/Black B+, with optical brightener, 250pcs

VF2344 - TQC Test charts A5, White/Black B+, with optical brightener, 250pcs

VF2345 - TQC Test charts A4, White/Black B+, with optical brightener, 250pcs

VF2346 - TQC Test charts A5, Black/White chequered B+, with optical brightener, 250pcs

VF2347 - TQC Test charts A4, Black/White chequered B+, with optical brightener, 250pcs

VF2354 - TQC Test charts A3, Black/White chequered B+, with optical brightener, 250pcs

VF2317 - TQC Test charts A6, White/Black B-, without optical brightener, 250pcs

VF2319 - TQC Test charts A5, White/Black B-, without optical brightener, 250pcs

VF2321 - TQC Test charts A4, White/Black B-, without optical brightener, 250pcs

VF2323 - TQC Test charts A5, Black/White chequered B-, without optical brightener, 250pcs

VF2325 - TQC Test charts A4, Black/White chequered B-, without optical brightener, 250pcs

SPECIFICATIONS

Material : high grade stainless steel.
Accuracy : better than 3 micron

Outer dimensions : 75 x 20 x 25 mm / 115 x 20 x 20 mm.

USE


Select the appropriate gap and place the applicator on a plane smooth surface such as a glass plate.

Apply a sample of paint in the centre of the TQC Quadruplex applicator near the correct opening.

Draw down the applicator over the surface.

Due to physical reasons the max. film attainable wet film thickness is not equal to the gap depth. Deposited film thickness may vary from 40% to 80% of the clearance/gap depth.

Dry film thickness will be lower than wet thickness due solvent/water evaporation.



SPECIAL CARE

- Though robust in design, this instrument is precision-machined. Never drop it or knock it over
- Always clean the instrument after use.
- Clean the instrument using a soft dry cloth. Never clean the instrument by any mechanical means such as a wire brush or abrasive paper. This may cause, just like the use of aggressive cleaning agents, permanent damage.
- Always keep the instrument in its case when not in use.

 TQC B.V.
 2908 LL Capelle aan den IJssel
 phone: +31 (0)10-7900100
 e-mail: info@tqc.eu

 Molenbaan 19
 The Netherlands
 fax: +31 (0)10-7900129
 www.tqc.eu





DISCLAIMER

The right of technical modifications is reserved.

The information given in this sheet is not intended to be exhaustive and any person using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. Whilst we endeavour to ensure that all advice we give about the product (whether in this sheet or otherwise) is correct we have no control over either the quality or condition of the product or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing to do so, we do not accept any liability whatsoever or howsoever arising for the performance of the product or for any loss or damage (other than death or personal injury resulting from our negligence) arising out of the use of the product. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.