

YSI 95 DO Meter

1.

1)

AA - Size

6

2) Calibration/Storage Chamber

3)

가

MEA Probe () 8-9

가

2-3 가

()

1 보호캡을
벗긴다.

2



캡을 벗긴다.

3



측정용액을
8-9방울로
격막캡을 채운다.

격막캡을 톡톡
쳐서 기포가
들어가지 않도록
한다.

4



손으로 캡을
돌려 잠근다.

5



손으로 보호캡을
다시 끼운다.

2.

- 1)
- 2) . (O-Ring .)
- 3) ON/OFF .
- 4) 15 . (DO 가)
- 5) ▲ ▼ .
- 6) LCD ▲ ▼
- ENTER .) 12 1200ft .
- 7)
- 8) CAL ,
- DO .
- 9) DO ENTER .
- 10) SAVE .

Temp	Solubility mg/ ℓ	Temp	Solubility mg/ ℓ	Temp	Solubility mg/ ℓ
0	14.62	17	9.67	34	7.07
1	14.22	18	9.47	35	6.95
2	13.83	19	9.28	36	6.84
3	13.11	20	9.09	37	6.73
4	12.77	21	8.92	38	6.62
5	12.45	22	8.74	39	6.52
6	12.14	23	8.58	40	6.41
7	11.84	24	8.42	41	8.31
8	11.56	25	8.26	42	6.21
9	11.29	26	8.11	43	6.02
10	11.03	27	7.97	44	5.93
11	10.78	28	7.83	45	5.84
12	10.54	29	7.69	46	5.74
13	10.31	30	7.56	47	5.65
14	10.08	31	7.43	48	5.65
15	9.87	32	7.31	49	5.56
16	9.87	33	7.18	50	5.47