

## WE600 Humidity Sensor WE700 Temperature Sensor WE770 Solar Shield



### Specifications

#### Humidity Sensor

Type: Capacitance  
Output: 4-20 mA  
Range: 0 to 100% RH  
Accuracy:  $\pm 2\%$  RH  
Operating Voltage: 10-36 VDC  
Current Draw: 3mA plus sensor output  
Warm Up Time: 3 seconds minimum  
Operating Temp:  $-40^{\circ}$  to  $+55^{\circ}$ C  
Sensor Size: 1 1/2" diameter x 7"  
Weight: 1/2 lb.

#### Temperature Sensor

Type: Precision RTD  
Output: 4-20 mA  
Range:  $-50^{\circ}$ C to  $+50^{\circ}$ C  
Accuracy:  $\pm 0.2^{\circ}$ F or  $\pm 0.1^{\circ}$ C  
Operating Voltage: 10-36 VDC  
Current Draw: Same as sensor output  
Warm Up Time: 5 seconds minimum  
Operating Temp:  $-50^{\circ}$  to  $+100^{\circ}$ C  
Sensor Size: 3/4" diameter x 4 1/2"  
Weight: 1/2 lb.

#### Solar Shield

Size: 4" diameter x 8 1/2"  
Weight: 1 lb.

### Description

The Global Water Humidity Sensor is a precise, durable unit. Humidity sensors are composed of a solid state capacitive element with a linear amplifier. The humidity sensor output is 4-20 mA with a three wire configuration.

The Global Water Temperature Sensor is a high quality, rugged instrument, precision RTD calibrated to US National Standards. The temperature sensor output is 4-20 mA with a two wire configuration.

Each sensor is mounted on 25' of marine grade cable, with lengths up to 500' available upon request. The electronics are completely encapsulated in marine grade epoxy within a stainless steel housing.

The Global Water Solar Shield is a ventilated sun shield, with high reflectiveness, low heat retention, and low thermoconductivity. The unit is designed to protect the Global Water Humidity and Temperature sensors from direct sunlight that may affect the sensor's 4-20 mA output.

### Price List

#### WE600

Humidity Sensor

#### WE700

Temperature Sensor

#### WE770

Solar Shield

#### WQEXC Extra Cable

Cable length is measured from end of cable to bottom of sensor. After 25', up to 500'

Contact  
Global Water  
for all your  
instrumentation  
needs:

Water Level

Water Flow

Water Samplers

Water Quality

Weather

Remote Monitoring

Control



**Global Water**  
The Leader in Water Instrumentation

In the U.S. call toll free  
at 1-800-876-1172  
International: 916 638-3429  
Fax: (916) 638-3270  
Email: [globalw@globalw.com](mailto:globalw@globalw.com)

Visit our online catalog at  
[www.globalw.com](http://www.globalw.com)  
11257 Coloma Road  
Gold River, CA 95670 USA  
7:30 AM to 4 PM PST