

		Carbon Still (KS D3576 / JIS G3459)							Stainless Still								Copper Pipe									
		KS(S.G.P)		SCH 20		SCH 40			SCH 5		SCH10		SCH20		SCH40				K type		L type		M type			
A	Inch																									
10	3/8	17	2.3	13	-	-	2.3	13	17	1.2	15	1.7	14	2	13	2.3	13	13	1.2	10	0.9	11	0.6	11		
15	1/2	22	2.8	16	-	-	2.8	16	22	1.7	18	2.1	17	2.5	17	2.8	16	16	1.2	13	1	14	0.7	14		
20	3/4	27	2.8	22	-	-	2.9	21	27	1.7	24	2.1	23	2.5	22	2.9	21	22	1.7	19	1.1	20	0.8	21		
25	1	34	3.2	28	-	-	3.4	27	34	1.7	31	2.8	28	3	28	3.4	27	29	1.7	25	1.3	26	0.9	27		
32	1.3	43	3.5	36	-	-	3.6	36	43	1.7	39	2.8	37	3	37	3.6	36	35	1.7	32	1.4	32	1.1	33		
40	1.5	49	3.5	42	-	-	3.7	41	49	1.7	45	2.8	43	3	43	3.7	41	41	1.8	38	1.5	38	1.2	39		
50	2	61	3.8	53	3.2	54	3.9	53	61	1.7	57	2.8	55	3.5	54	3.9	53	54	2.1	50	1.8	50	1.5	51		
65	2.5	76	4.2	68	4.5	67	5.2	66	76	2.1	72	3.1	70	3.5	69	5.2	66	67	2.4	62	2	63	1.7	63		
80	3	89	4.2	81	4.5	80	5.5	78	89	2.1	85	3.1	83	4	81	5.5	78	79	2.8	74	2.3	75	1.8	76		
90	3.5	102	4.2	93	4.5	93	5.7	90	102	2.1	97	3.1	96	4	94	5.7	90	-	-	-	-	-	-	-		
100	4	114	4.5	105	4.9	105	6	102	114	2.1	110	3.1	108	4	106	6	102	105	3.4	98	2.8	99	2.4	100		
125	5	140	4.5	131	5.1	130	6.6	127	140	2.8	134	3.4	133	5	130	6.6	127	130	4.1	122	3.2	124	2.8	125		
150	6	165	5	155	5.5	154	7.1	151	165	2.8	160	3.8	158	5	155	7.1	151	156	4.9	146	3.6	148	3.1	149		
200	8	217	5.8	205	6.4	204	8.2	200	217	2.8	211	4.2	208	6.5	204	8.2	200	206	6.9	193	5.1	196	4.3	198		
250	10	267	6.6	254	6.4	255	9.3	249	267	2.8	262	4.6	258	6.5	254	9.3	249	257	8.6	240	6.4	244	5.4	246		
300	12	319	6.9	305	6.4	306	10	298	319	3.4	312	4.8	309	6.5	306	9.5	299	-	-	-	-	-	-	-		
350	14	356	7.9	340	7.9	340	11	333	356	4	348	4.8	346	6.4	343	9.5	337	-	-	-	-	-	-	-		
400	16	406	7.9	391	7.9	391	13	381	406	4	398	4.8	397	6.4	394	9.5	387	-	-	-	-	-	-	-		
450	18	457	7.9	441	7.9	441	14	429	457	4.8	448	4.8	448	6.4	445	9.5	438	-	-	-	-	-	-	-		
500	20	508	7.9	492	9.5	489	15	478	508	4.8	498	5.5	497	6.4	495	9.5	489	-	-	-	-	-	-	-		
550	22	589	-	-	9.5	570	-	-	589	4.8	579	5.5	578	6.4	576	9.5	570	-	-	-	-	-	-	-		
600	24	610	-	-	9.5	591	-	-	610	4.8	600	6.4	597	6.4	597	9.5	591	-	-	-	-	-	-	-		

