

Thermo Scientific Niton XL2 GOLDD XRF Analyzer

The performance leading solution from the pioneer in handheld XRF instrumentation.

Thermo Scientific Niton XL2 GOLDD analyzers provide you with many distinct advantages:

- Light element detection (Mg, Al, Si, P, S) without helium purge vacuum
- From turn on to trigger pull to near instantaneous results
- Very easy to use – even by non-technical personnel
- Rugged design for the most challenging industrial environments
- Standard integrated camera for accurate positioning of analysis area
- Completely nondestructive test



Premier Performance in a Value Package

The performance-leading Thermo Scientific™ Niton™ XL2 GOLDD analyzer offers premier performance and advanced electronics while maintaining the point-and-shoot simplicity that is the hallmark of all of our x-ray fluorescence (XRF) instruments. With our groundbreaking GOLDD™ technology, your analytical capabilities are taken to a whole new level. The direct benefits to you include: real-time results, light element analysis, and advanced performance in our value package.

The Niton XL2 GOLDD analyzer also includes a standard integrated camera to ensure accurate positioning on the area of interest to capture and store an image for review or inclusion in reports.

Ergonomically designed and featuring daylight-readable icons, the Niton XL2 GOLDD incorporates customizable menus, multiple language options, and a standard analytical range of up to 30 elements from magnesium to uranium. Sealed against moisture and dust with 100% embedded software tools, these analyzers are lightweight yet ruggedly built to

withstand the harshest environments – in the field or on the shop floor.

The GOLDD Advantage

GOLDD technology delivers vast improvements in sensitivity or measurement times – as much as 10-times faster than conventional Si-PIN detectors and up to 3-times more precise than conventional silicon drift detectors (SDD). We achieved this improvement by combining the Niton XL2 GOLDD 45kV, 100 µA x-ray tube, closely optimized geometry, and patented signal processing hardware and software. These advantages are coupled with our drift detector, one of the largest area drift detectors that is commercially available in a handheld XRF analyzer, providing you with superior performance in the form of faster analysis and lower detection limits.

The final product is the Niton XL2 GOLDD – a more versatile and technologically advanced handheld XRF analyzer, designed without compromise to make you more successful.

Thermo
SCIENTIFIC



Niton XL2 GOLDD: Large area drift detector and optimized geometry for more x-ray counts gives you faster and more precise readings.

With its unparalleled accuracy, you can be confident that the Niton XL2 GOLDD won't misidentify value, grade, or residuals. The Niton XL2 GOLDD stands alone with its many standard features and available options. By utilizing the standard Thermo Scientific Niton Data Transfer (NDT®) PC software suite to customize the instrument, you can set operator permissions, generate custom reports, print certificates of analysis personalized with your own company logo, or remotely monitor and operate the instrument hands-free from your PC. Integrated USB and Bluetooth® communications provide direct data transfer to your PC or networked storage device, eliminating the cumbersome data synchronization procedures required by Windows Mobile®-based XRF analyzers.

Niton XL2 GOLDD Analyzers

Whether you need an analyzer for metal alloy analysis, mining operations, or environmental screening, the performance-leading Niton XL2 GOLDD provides cost-effective high-speed performance, point-and-shoot simplicity, integrated camera, and the cutting-edge technology that you have come to expect from industry-leading Thermo Scientific Niton XRF analyzers.

Thermo Scientific Niton XL2 GOLDD Specifications	
Weight	3 lbs 5.8 oz (1.53 kg)
Dimensions	10.25 x 11 x 4 in. (256 x 275 x 100 mm)
Tube	Ag anode 45 kV maximum, 100 uA maximum
Detector	Geometrically Optimized Large Area Drift Detector (GOLDD)
System Electronics	400 MHz ARM 11 CPU 300 MHz dedicated DSP 80 MHz ASICS DSP for signal processing 4096 channel MCA 64 MB internal system memory/128 MB internal user storage
Display	Fixed angle, color, touch-screen display
Standard Analytical Range	Up to 30 elements from Mg to U (varies by application)
Data Storage	Internal >10,000 readings with spectra
Data Transfer	USB, Bluetooth™, and RS-232 serial communication
Security	Password-protected user security
Mode (Varies by application)	Alloy Modes: Metal Alloy, Electronics Alloy, Precious Metals Bulk Modes: Mining, Soil Plastic Modes: RoHS Plastics, Toy & Consumer Goods Plastics, TestAll™, Painted Products Limited Custom Modes: Upon request (based on application feasibility)
Data Entry	Touch-screen keyboard User-programmable pick lists Optional wireless remote barcode reader
Standard Accessories	Integrated camera Locking shielded carrying case Shielded belt holster Two 6-cell lithium-ion battery packs 110/220 VAC battery charger/ AC adaptor PC connection cables (USB and RS-232) Niton Data Transfer (NDT) PC software Safety lanyard Check samples/standards
Optional Features and Accessories	Engine Guard protects critical detection components and minimizes operational downtime Thermo Scientific portable test stand, stationary (bench-top) stand, mobile test stand, Thermo Scientific Field Mate Welding mask Soil testing guard
Licensing/Registration	Varies by region. Contact your local distributor.
Compliance	CE, RoHS

Thermo Scientific Niton XL2 GOLDD analyzers represent just one of our handheld analyzer solutions, which include XRF tools for metal alloy identification, mining and exploration, lead-based paint testing, RCRA metals in soil, toy and consumer goods testing, RoHS and WEEE compliance screening, and many other analysis needs.



thermoscientific.com/niton

Bluetooth is a registered trademark of Bluetooth SIG. Windows Mobile is a registered trademark of Microsoft Corporation.

© 2015 Thermo Fisher Scientific Inc. All rights reserved. All trademarks are the property of Thermo Fisher Scientific and its subsidiaries. Specifications, terms and pricing are subject to change. Not all products are available in all countries. Please consult your local sales representative for details.

Africa-Other +27 11 570 1840
Australia +61 2 8844 9500
Austria +43 1 333 50 34 0
Belgium +32 53 73 42 41
Canada +1 800 530 8447
China +86 10 8419 3588
Denmark +45 70 23 62 60
Europe-Other +43 1 333 50 34 0

Finland /Norway/Sweden
+46 8 556 468 00
France +33 1 60 92 48 00
Germany +49 6103 408 1014
India +91 22 6742 9434
Italy +39 02 950 591
Japan +81 45 453 9100
Latin America +1 608 276 5659

Middle East +43 1 333 50 34 0
Netherlands +31 76 579 55 55
South Africa +27 11 570 1840
Spain +34 914 845 965
Switzerland +41 61 716 77 00
UK +44 1442 233555
USA +1 800 532 4752

Thermo
SCIENTIFIC

A Thermo Fisher Scientific Brand