

Ordering information

Product structure

Approval	
AA	Non-hazardous area
Sensor input	
M1	1 x digital sensor
M2	2 x digital sensor
N1	1 x digital sensor, M12 socket
N2	2 x digital sensor, M12 socket
Communication	
A1	2 x analog output 0/4 to 20 mA
A3	4 x analog output 0/4 to 20 mA
Additional functions	
F0	None
F2	2 x relay for cleaning; limit value
Power supply	
1	100 to 230 V AC
6	24 V DC
7	24 V AC (cannot be extended to CM448)
Cable entry	
0	Metric
1	NPT
2	G
Cable entry set	
A	Enclosed
B	Mounted
CM442-	Order code

Initial setting for operating language (only one option may be selected)	
AA	English
AB	German
AC	French
AD	Spanish
AE	Italian
AF	Dutch
AG	Portuguese
AK	Chinese
Service (more than one option may be selected)	
K5	Free from paint-wetting impairment substances
Additional approvals (more than one option may be selected)	
MC	cCSAus, general purpose
Test, certificates (more than one option may be selected)	
Q3	Inspection certificate to EN 10204-3.1
Accessories mounted (more than one option may be selected)	
RC	CDI; external socket
RS	SD card, 1 GB, Industrial Flash Drive
Identification (more than one option may be selected)	
Z1	Measuring point (TAG), see additional specification

Simply append the additional options to the order code you selected above. Please contact your sales office if you have any questions.