

**Open Channel Instrumentation**  
**Vantage 2200**  
**Ultrasonic Flow/Level Meters**



Enclosure	Sensors			Options
<p><b>2210</b> *</p> <p>Nema 4X Enclosure                      One 4-20 mA output                      Data Logger w/software                      RS232                      *Optional Relays/Up to 5</p> <p><b>2220</b> *</p> <p>Nema 4X Enclosure                      Two 4-20 mA outputs                      Data Logger w/software                      RS232 &amp; RS485                      *Optional Relays/Up to 5</p> <p><u>For Nonincendive Cl. I &amp; II,                      Grp. A-D, Div. 2 rating,                      add <b>N</b> to end of model                      number when ordering.</u></p> <p><b>EX Optional Enclosure</b>                      Explosion proof enclosure                      Class I, Groups C &amp; D                      Class II, Groups E, F &amp; G                      Divisions 1 &amp; 2</p> <p><b>Price on Application</b></p>	<p><b>FB4A</b></p> <p>0-25 Ft. Range                      30 feet sensor                      cable                      Body material                      PVC</p> <p><b>FB4B</b></p> <p>100 feet sensor                      cable</p> <p><b>FB4C</b></p> <p>200 feet sensor                      cable</p> <p><b>FB4X</b>                      Special length                      cable over 200                      feet</p>	<p><b>FB2A</b></p> <p>0-15 Ft. Range                      30 feet sensor                      cable                      Body material                      Tefzel</p> <p><b>FB2B</b></p> <p>100 feet sensor                      cable</p> <p><b>FB2C</b></p> <p>200 feet sensor                      cable</p> <p><b>FB2X</b>                      Special length                      cable over 200                      feet</p>	<p><b>FB3A</b></p> <p>0-50 Ft. Range                      100 feet sensor                      cable                      Body material                      ABS</p> <p><b>FB3B</b></p> <p>300 feet sensor                      cable</p>	<p>Factory Calibration                      Yes: <b>A</b>                      No: <b>B</b></p> <p>Heater &amp; Thermostat  <b>H</b></p> <p>Keylock  <b>K</b></p> <p><b>Sensor Cable (Belden 9365)</b>  <b>It is recommended NOT to                      have splices in the UH cable.</b></p> <p>Modem  <b>M</b></p> <p><b>Relay Kit</b> (Includes One relay                      and terminal connector)  <b>R</b></p>
<p><b>Sensor mounting bracket included</b></p>				

**\*NO RELAYS ARE INCLUDED**

**Ordering Example:**

Vantage 2210 w/FB4A, 2 relays, heater and thermostat and Factory Calibration = **2210FB4AHBR2**

**F.O.B. Tulsa, OK**