

모델별 비교사양서

세창인스트루먼트(주)

YSI Model	5100	5000	52	55	58	95	85	550
표시방법	LCD 액정	LCD 액정	LCD 액정	LCD 액정	LCD 액정	LCD 액정	LCD 액정	LCD 액정
정밀도 mg/L	±0.1% +1 lsd*	±0.1% +1 lsd*	±0.03	±0.3**	±0.03	±0.2**	±0.3**	±0.3**
% air	±0.1% +1 lsd*	±0.1% +1 lsd*	±0.1% +1 lsd*	±2%	±0.3%	±2%	±2%	±2%
온도	±0.1°C	±0.1°C	±0.1°C	±0.2°C	±0.3°C	±0.2°C	±0.1°C ±1 lsd	±0.3°C
측정범위 mg/L	0-60	0-60	0-20	0-20	0-20	0-50	0-20	0-20
% air	0-600%	0-600%	0-200%	0-200%	0-200%	0-500%	0-200%	0-200%
온도	-5 to +50°C	-5 to +50°C	-5 to +45°C	-5 to +45°C	-5 to +45°C	-5 to +45°C	-5 to +45°C	-5 to +45°C
분해능 mg/L	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01
% air	0.1%	0.1%	0.1%	0.1%	0.1%	0.1%	0.1%	0.01%
온도	0.01°C	0.01°C	0.1°C	0.1°C	0.1°C	0.1°C	0.1°C	0.1°C
전원	Battery & AC	Battery & AC	Battery & AC	Battery	Battery & AC	Battery	Battery	Battery
기록계용 출력	No	No	No	No	Yes	No	No	No
염도보정	Yes	Yes	Yes	Yes	Yes	Yes	Automatic	Yes
온도보상	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic
기타기능	RS-232 OUR/SOUR Memory	RS-232 BOD Memory	RS-232 Memory Field/lab	Handheld Backlit display	Chart recorder output	Patented MEA sensor Handheld	Autoranging Handheld Conductivity	IP67 Waterproof Handheld CE