

Custom Cable Worksheet - pH

How To Order Custom pH Cables

Complete the part number below by selecting from options (Steps 1-4) and filling in the boxes.

Part #: AX-1000 - -

Step 1. Electrode Plug Step 2. Cable Type Step 3. Cable Length Step 4. Instrument Connector

1

Choose Electrode Plug
Click one to select:

H P



HP Electrode Plug for FermProbes with S8 metric cap

Cable Type
A or M

K P



KP Electrode Plug for FermProbes with K9 metric cap

Cable Type
M

H 5



HP Electrode Plug and Solution Ground Lead for FermProbes with S8 metric cap

Cable Type
N or B

K 5



KP Electrode Plug and Solution Ground Lead for FermProbes with K9 metric cap

Cable Type
N or B

2

Choose Cable Type
Click one to select:

Type A
A

3 mm, low noise, shielded coaxial cable is lightweight and very flexible. The 3 mm cable is frequently chosen for benchtop installations where space is at a premium and cables are required to make many sharp turns and twists.

Type M
M

5 mm, low noise, shielded coaxial cable is thicker and more rugged. The 5 mm cable is often specified for pilot and process installations.

Type N
N

5 mm, low noise, shielded coaxial cable is jacketed with an extra lead for connecting solution ground to differential input style transmitters.

Type B
B

6 mm, low noise, shielded multi-conductor cable is jacketed with an extra lead for connecting solution ground to differential input style transmitters.

3

Choose Cable Length

0 3

3 FT (1 M)

0 6

6 FT (2 M)

1 0

10 FT (3 M)

Specify length

4

Choose Instrument Connector*
Click one to select:



BNC Plug

B C



DIN 19262 Plug

D N



Spade Lugs

S L



Crimped Ferrules

F F



Crimped Ferrules with a Solution Ground Lead

F F

*Other options available

5

Call, fax, or send an e-mail with the completed part number to receive pricing and delivery information. Or feel free to contact us for any other assistance.